

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO.

30-04507859

5. Indicate Type of Lease

STATE ☐

FEE ☒

6. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

OIL
WELL ☐

GAS
WELL ☒

OTHER

2. Name of Operator

Bannon Energy, Inc. c/o Holcomb Oil & Gas

3. Address of Operator

P.O. Box 2058, Farmington NM 87499

7. Lease Name or Unit Agreement Name

Sullivan

8. Well No.

3

9. Pool name or Wildcat

Aztec Fruitland

4. Well Location

Unit Letter E : 1945 Feet From The North Line and 660 Feet From The West Line

Section 25 Township 29N Range 11W NMPM San Juan County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

11.

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☒

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

OTHER: ☐

SUBSEQUENT REPORT OF

REMEDIAL WORK ☐

ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐

PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOBS ☐

OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

- The well will be P&A'd concurrent with completion of offset well, Sullivan JB #1. Estimated start date is 12-19-89.
- Strip 84 sx. Class "B" cement from PBTD 1525'-710', estimated top of cement outside 5 1/2".
- TIH with tubing gun and perforate 2' @ 2 JSPF the interval 660'-662' below base of Ojo Alamo.
- Displace 50 sx. of cement out of perms to protect Ojo Alamo.
- Strip plug + 70 sx. Class "B" cement.
Cut 5 1/2" production casing below ground level, spot surface plug and set P&A marker.

Top of producing formation: Fruitland Sand @ 1480'.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

W.J. Holcomb

TITLE

Operating Agent for Bannon

DATE 12-12-89

TYPE OR PRINT NAME

W.J. Holcomb

TELEPHONE NO. 505-326-0550

(This space for State Use)

Original Signed by CHARLES GHOLSON

DEPUTY OIL & GAS INSPECTOR, DIST. #3

APPROVED BY

TITLE

DATE

DEC 13 1989

CONDITIONS OF APPROVAL, IF ANY: