Form	3160-5
(June	1990)

1. Type of Well

Oil Gas Well

UNITED STATES DEPARTMENT OF THE INTERIOR **BUREAU OF LAND MANAGEMENT**

FORM APPROVED				
Budget Bureau No.	1004-0135			
Expires: March	11 1001			

5.	Lease	Designation	and	Serial	No.

SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.

Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

ecroleum Corp. % NMOCD

7. If Unit or CA, Agreement Designation

4 Azrec Totah UT.

8. Well Name and No.

1000 R.s 13 r. 205 R.J. 4. Location of Well (Footage, Sec., T., R., M., or Survey Des 880/N = 2300/W Sec. 29, 7.29	cription)	10. Field and Pool, or Exploratory Area Totah Gallup 11. County or Parish, State San Juan NM
CHECK APPROPRIATE BOX(s	TO INDICATE NATURE OF NOTICE	E, REPORT, OR OTHER DATA
TYPE OF SUBMISSION		FACTION
Notice of Intent Subsequent Report Final Abandonment Notice	Abandonment Recompletion Plugging Back Casing Repair Altering Casing Other	Change of Plans New Construction Non-Routine Fracturing Water Shut-Off Conversion to Injection Dispose Water (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)
 Describe Proposed or Completed Operations (Clearly state all give subsurface locations and measured and true vertical 	pertinent details, and give pertinent dates, including estimated depths for all markers and zones pertinent to this work.)*	date of starting any proposed work. If well is directionally drilled

See attached Report for PaA

OIL COM. DIV. DIST. 3

14. I hereby certify that the foregoing is true and correct		
Signed NMOCO CONTIACT	Title	Date 5/21/98
(This space for Federal or State office use)		
Approved by Spencer Conditions of approval, If any:	Title	Date MAY 2 1998

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

TRIPLE P WELL SERVICE, INC.

AZTEC TOTAH #4 RIG 4 START 4/3/98 END 4/7/98

- 1. Pull 123 rods (3075') Trip out and tally 101 joints (3085')
- 2. Run in hole with 4-1/2 scraper

- Spot 100sx, 118cf @ 3020'. Tag cement @ 1640'
 Spot cement plug @ 1512'. 50sx, 59cf
 Shot squeeze @ 379'. Circulate 150sx, 177cf to surface.