DEPARTMENT OF THE INTERIOR COMPLETED INSTRUCTIONS ON THE GEOLOGICAL SURVEY  SUNDRY NOTICES AND REPORTS ON WELLS  (Do not use this form for promotine to differ on the factor of the make to a different reservoir.  1.				/	
DEPARTMENT OF THE INTERIOR Growth described as a personal process of the Conference		UNITED STATE	SUBMIT IN TRIPLICATE	Dudget Dugget Ma 40 D1404	
SUNDRY NOTICES AND REPORTS ON WELLS  (Do not use this form for recognizate to drill or to decepts or flux back to a different reservoir.  Out. (Do not use this form for recognizate to drill or to decepts or flux back to a different reservoir.  Out. (Do not use this form for recognizate to drill or to decepts or flux back to a different reservoir.  Out. (Do not use this form for recognizate to drill or to decepts or flux back to a different reservoir.  Out. (Do not use this form for recognization of the proposals.)  I. compared to the proposals.  Out. (Do not use this form for recognization of the proposals.)  I. compared to the proposals.  I.	(May 1903)	(f)than instructions on mal			
SUNDRY NOTICES AND REPORTS ON WELLS  The waste of the control of degree of plug back to a different reservoir.  In the control of the control	GEOLOGICAL SURVEY			14-20-603-7106	
(Do not use this form for provincials to drill or to dryen or plus back to a different reservoir.    Navajo Tribe	CHNDI	DV NOTICES AND DED	OPTS ON WELLS	6. IF INDIAN, ALLOTTEE OR TRIBE NAME	
Use "APPLICATION FOR PERMIT—" for each proposals.)   Navajo Tribe					
Other States and State	ั บ				
J. Gregory Merrion  8. Adoass or Officeron  P.O. Box 507, Farmington, New Mexico 87401  4. Docardon or well. Heport location clearly and in accordance with any State requirements.* At source.  1980 FSL and 660 FWL  15. Elevations (Show whether BF, BF, GL etc.)  16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data  Notice of Internations (Show whether BF, BF, GL etc.)  16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data  Notice of Internations of Internations of Indicate Nature of Notice, Report, or Other Data  Notice of Internations of Internations of Indicate Nature of Notice, Report, or Other Data  Notice of Internations of Internations of Indicate Nature of Notice, Report, or Other Data  Notice of Internations of Indicate Nature of Notice, Report, or Other Data  Notice of Internations of Indicate Nature of Notice, Report, or Other Data  Notice of Internations of Indicate Nature of Notice, Report, or Other Data  Notice of Internations of Indicate Nature of Notice, Report, or Other Data  Notice of Internations of Indicate Nature of Notice, Report, or Other Data  Notice of Internations of Indicate Nature of Notice, Report, or Other Data  Notice of Internations of Indicate Nature of Notice, Report, or Other Data  Notice of Internations of Indicate Nature of Notice, Report, or Other Data  Notice of Internations of Indicate Nature of Notice, Report, or Other Data  Notice of Internations of Internations of Indicate Nature of	OIL T GAS	OTHER		7. UNIT AGREEMENT NAME	
J. Gregory Merrion  R. Address or offserior  P.O. Box 507, Farmington, New Mexico 87401  8. Decentor over Will, Herory location clearly and is secondarce with any State requirements.  8. Decentor over Will, Herory location clearly and is secondarce with any State requirements.  8. South Waterflow South Water Report or Other Data South Water Report or Other Data South Water South Water Report or Other Data South Water Report South Water Report or Other Data South Water Report South Water Report South Water Report or Other Data South Water Report South Water Report South Water Report or Other Data South Water Report or Other Data South Water Report South Water Repor	2. NAME OF OPERATOR	8. FARM OR LEASE NAME Water Lion			
P.O. Box 507, Farmington, New Mexico 87401  1. Defection of Well (Report location clearly and in accordance with any State requirements.*  1980 FSL and 660 FWL  11. BEC. T. B. M. O. BLUK. AND SOUTH Waterflow South Waterflow South Waterflow Sect. 20, T29N, R15W  12. COUNTY OR PARISE 13. STATE  Sec. 20, T29N, R15W  12. COUNTY OR PARISE 13. STATE  San Juan N.M.  16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data  STRENGED THEATTON TO:  TEST WATER SHUT-OFF  PRACTICE THEAT SHOOT OF INTENTION TO:  TEST WATER SHUT-OFF  PRACTICE THEAT SHOOT OF INTENTION ADDITION TO:  TEST WATER SHUT-OFF  PRACTICE THEAT SHOOT OF INTENTION ADDITION TO:  TEST WATER SHUT-OFF  PRACTICE THEAT SHOOT OF INTENTION TO:  TEST WATER SHUT-OFF  PRACTICE THEAT SHOOT OF INTENTION ADDITION TO:  THE TWENTY OF AREA COUNTY OF A STRENGE THE THEAT THE TRANS CASING (Other)  PRACTICE THEAT SHOOT OF A COUNTY OF THE THEAT OF					
4. DOCATION OF WILL, (Report location clearly and in accordance with any State requirements."  South Waterflow Bell South Waterflow Bell 11. Bell Factors 1. Bell South Waterflow Bell 11. Bell Factors 1. Bell South Waterflow Bell 11. Bell Factors 1. Bell					
South Waterflow Sull 11. Sec. 12. M. No. Balk. AND Sulvarious (Show whether Dr. Rt. GR. etc.)  14. Ferrit No. 15. Blevations (Show whether Dr. Rt. GR. etc.)  15. Sad' KB  16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data Notice of Intertion to:  16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data Notice of Intertion to:  17. Decrease and the sulface complete analysis of active change plants of active completes on well (Other)  17. Decrease and the sulface completes on the sulface of the					
14. PERMIT NO.  15. ELEVATIONS (Show whether DV, RT, OL, etc.)  16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data  NOTICE OF INTERFOR TO:  TEST WATER SHUT-OFF PILL OR ALTER CASING SHOOT OR ACIDIZE BEFORE THEAT SHOOT ACIDIZE BEFORE THEAT SHOOT OR ACIDIZE BEFORE THEAT SHOOT OR ACIDIZE BEFORE THEAT SHOOT OR ACIDIZE BEFORE THEAT WELL  (Other)  17. DESCRIBE TRACTOR THEAT OPERATIONS (Clearly state all pertinent details, and give pertinent date date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent of the pertinent date of the pertinent dat	See also space 17 below.	1			
Sec. 20, T29N, R15W  14. PERMIT NO.  15. ELEVATIONS (Show whether pr. Rf. cs. etc.)  16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data  NOTICE OF INTERTION TO:  WATER SHUT-OFF PRACTURE TREAT SHOOT OF ACTIDEE  ARABODON*  ARABO					
15. PERMIX NO.  15. LEAVATONS (Show whether Dr. RT. CS. etc.)  12. COUNT OR PARISE 13. STATE  5384' KB  16.  Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data  **NOTICE OF INTENTION TO:  **TEST WATER SHUT-OFF**  PRACTOR THEAT  **SHOOT OR ACTIVED**  **ALTERING CASING ARTHOUGH OR ACTIVED**  **ALTER	1980 FSL and 66	SURVEY OR AREA			
15. PERMIX NO.  15. LEAVATONS (Show whether Dr. RT. CS. etc.)  12. COUNT OR PARISE 13. STATE  5384' KB  16.  Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data  **NOTICE OF INTENTION TO:  **TEST WATER SHUT-OFF**  PRACTOR THEAT  **SHOOT OR ACTIVED**  **ALTERING CASING ARTHOUGH OR ACTIVED**  **ALTER		•		Sec. 20 T29N R15W	
16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data  NOTICE OF INTENTION TO:  TEST WATER SHUT-OFF FRACTURE THEAT SHOOT OR ACIDIZE ARABODON*  REPAIR WELL CHANGE PLANS  (Other)  17. DESCRIBE PROPOSED OR CONPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent datas, including extinated date of source and to give subsurface locations and measured and true vertical depths for all markets and zones pertinent shows the per foot.  4-25-77  Pulled rods and tubing. Perforated 4198-4201 and 4208-4220 with one shot per foot.  4-26-77  Ran 2-7/8" tubing with Baker Model "R" packer and sand-oil fracked with 13,000 gallons lease oil treated with FR-5 friction reducer and 10,000 lbs. 20-40 sand and 250 lbs. P-3 scale inhibitor.  Dropped six ball sealers during treatment. Fracked at 13 BPM and 3200 PSI.  4-27-77  Layed down 2-7/8" tubing. Re-ran 2" tubing. Ran rods and put on pump.  MAY 6 1977  OIL COM. COM.  MAY 5 1977  U. S. COCICOICAL SUPPLY	14. PERMIT NO.	15. ELEVATIONS (Show	whether DF, RT, GR, etc.)		
16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data  NOTICE OF INTENTION TO:  TEST WATER SHUT-OFF FRACTURE THEAT SHOOT OR ACIDIZE ARABODON*  REPAIR WELL CHANGE PLANS  (Other)  17. DESCRIBE PROPOSED OR CONPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent datas, including extinated date of source and to give subsurface locations and measured and true vertical depths for all markets and zones pertinent shows the per foot.  4-25-77  Pulled rods and tubing. Perforated 4198-4201 and 4208-4220 with one shot per foot.  4-26-77  Ran 2-7/8" tubing with Baker Model "R" packer and sand-oil fracked with 13,000 gallons lease oil treated with FR-5 friction reducer and 10,000 lbs. 20-40 sand and 250 lbs. P-3 scale inhibitor.  Dropped six ball sealers during treatment. Fracked at 13 BPM and 3200 PSI.  4-27-77  Layed down 2-7/8" tubing. Re-ran 2" tubing. Ran rods and put on pump.  MAY 6 1977  OIL COM. COM.  MAY 5 1977  U. S. COCICOICAL SUPPLY		53841 KB		San Juan N.M.	
NOTICE OF INTENTION TO:  TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDILE SHOOT OR ACIDILE ABANDON* CHANGE PLANS  (Other)  17. DESCRIBE PROFOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work, if well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*  4-25-77 Pulled rods and tubing. Perforated 4198-4201 and 4208-4220 with one shot per foot.  4-26-77 Ran 2-7/8" tubing with Baker Model "R" packer and sand-oil fracked with 13,000 gallons lease oil treated with FR-5 friction reducer and 10,000 lbs. 20-40 sand and 250 lbs. P-3 scale inhibitor. Dropped six ball sealers during treatment. Fracked at 13 BPM and 3200 PSI.  4-27-77 Layed down 2-7/8" tubing. Re-ran 2" tubing. Ran rods and put on pump.  MAY 5 1977  MAY 6 1977  OIL COM COM DIST. 3  MAY 5 1977	16.		ndicate Nature of Notice, Report, or C		
PRACTURE TREAT SHOOT OR ACIDIZE SHOOT OR	NOT				
PRACTURE TREAT SHOOT OR ACIDIZE SHOOT OR		THE STATE OF		¬	
SHOOT OB ACIDIZE  REPAIR WELL  (Other)					
(Other)  (Other)  (Other)  (Other)  (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)  (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)  (Other)  (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)  (Other)  (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)  (Other)  (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)  (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)  (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)  (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)  (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)  (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)  (Note: Report results of multiple completion or Recompletion Report and Log form.)  (Note: Report results of multiple completion or Recompletion Report and Log form.)  (Note: Report results of multiple completion or Recompletion Report and Log form.)  (Note: Report results of multiple completion or Recompletion Report and Log form.)  (Note: Report and		<del></del>		-	
(Other)  (Nort: Report results of multiple completion on Well Completion or Recompletion Reports and Log form.)  77. DEFORMER PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*  4-25-77 Pulled rods and tubing. Perforated 4198-4201 and 4208-4220 with one shot per foot.  4-26-77 Ran 2-7/8" tubing with Baker Model "R" packer and sand-oil fracked with 13,000 gallons lease oil treated with FR-5 friction reducer and 10,000 lbs. 20-40 sand and 250 lbs. P-3 scale inhibitor.  Dropped six ball sealers during treatment. Fracked at 13 BPM and 3200 PSI.  4-27-77 Layed down 2-7/8" tubing. Re-ran 2" tubing. Ran rods and put on pump.  MAY 5 1977  MAY 6 1977  OIL COM COM DIST. 3		<del></del>			
17. DESCRIBE PROPOSED ON COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*  4-25-77 Pulled rods and tubing. Perforated 4198-4201 and 4208-4220 with one shot per foot.  4-26-77 Ran 2-7/8" tubing with Baker Model "R" packer and sand-oil fracked with 13,000 gallons lease oil treated with FR-5 friction reducer and 10,000 lbs. 20-40 sand and 250 lbs. P-3 scale inhibitor. Dropped six ball sealers during treatment. Fracked at 13 BPM and 3200 PSI.  4-27-77 Layed down 2-7/8" tubing. Re-ran 2" tubing. Ran rods and put on pump.  MAY 5 1977  MAY 6 1977  OIL COM COM DISSIPPORT	(Other)		(Note: Report results	of multiple completion on Well	
4-25-77 Pulled rods and tubing. Perforated 4198-4201 and 4208-4220 with one shot per foot.  4-26-77 Ran 2-7/8" tubing with Baker Model "R" packer and sand-oil fracked with 13,000 gallons lease oil treated with FR-5 friction reducer and 10,000 lbs. 20-40 sand and 250 lbs. P-3 scale inhibitor. Dropped six ball sealers during treatment. Fracked at 13 BPM and 3200 PSI.  4-27-77 Layed down 2-7/8" tubing. Re-ran 2" tubing. Ran rods and put on pump.  MAY 5 1977  OIL CON GOND DIST. 3	proposed work. If we	MPLETED OPERATIONS (Clearly state a	all pertinent details, and give pertinent dates,	including estimated date of starting any	
shot per foot.  4-26-77 Ran 2-7/8" tubing with Baker Model "R" packer and sand-oil fracked with 13,000 gallons lease oil treated with FR-5 friction reducer and 10,000 lbs. 20-40 sand and 250 lbs. P-3 scale inhibitor.  Dropped six ball sealers during treatment. Fracked at 13 BPM and 3200 PSI.  4-27-77 Layed down 2-7/8" tubing. Re-ran 2" tubing. Ran rods and put on pump.  MAY 6 1977  OIL COM COM DIST. 3	,				
shot per foot.  4-26-77 Ran 2-7/8" tubing with Baker Model "R" packer and sand-oil fracked with 13,000 gallons lease oil treated with FR-5 friction reducer and 10,000 lbs. 20-40 sand and 250 lbs. P-3 scale inhibitor.  Dropped six ball sealers during treatment. Fracked at 13 BPM and 3200 PSI.  4-27-77 Layed down 2-7/8" tubing. Re-ran 2" tubing. Ran rods and put on pump.  MAY 6 1977  OIL COM COM DIST. 3	4-25-77	Pulled rode and tul	sing Perforated 4198-4201	and 4208-4220 with one	
4-26-77 Ran 2-7/8" tubing with Baker Model "R" packer and sand-oil fracked with 13,000 gallons lease oil treated with FR-5 friction reducer and 10,000 lbs. 20-40 sand and 250 lbs. P-3 scale inhibitor. Dropped six ball sealers during treatment. Fracked at 13 BPM and 3200 PSI.  4-27-77 Layed down 2-7/8" tubing. Re-ran 2" tubing. Ran rods and put on pump.  MAY 6 1977  OIL COM. GOM.  DIST. 3	7 23 17	<del>-</del>			
with 13,000 gallons lease oil treated with FR-5 friction reducer and 10,000 lbs. 20-40 sand and 250 lbs. P-3 scale inhibitor.  Dropped six ball sealers during treatment. Fracked at 13 BPM and 3200 PSI.  4-27-77 Layed down 2-7/8" tubing. Re-ran 2" tubing. Ran rods and put on pump.  MAY 5 1977  OIL COM COM DIST. 3		onot per root.		•	
with 13,000 gallons lease oil treated with FR-5 friction reducer and 10,000 lbs. 20-40 sand and 250 lbs. P-3 scale inhibitor.  Dropped six ball sealers during treatment. Fracked at 13 BPM and 3200 PSI.  4-27-77 Layed down 2-7/8" tubing. Re-ran 2" tubing. Ran rods and put on pump.  MAY 5 1977  OIL COM COM DIST. 3	4-26-77				
and 10,000 lbs. 20-40 sand and 250 lbs. P-3 scale inhibitor.  Dropped six ball sealers during treatment. Fracked at 13 BPM and 3200 PSI.  4-27-77 Layed down 2-7/8" tubing. Re-ran 2" tubing. Ran rods and put on pump.  MAY 6 1977  OIL COM. COM. DIST. 3					
Dropped six ball sealers during treatment. Fracked at 13 BPM and 3200 PSI.  4-27-77 Layed down 2-7/8" tubing. Re-ran 2" tubing. Ran rods and put on pump.  MAY 6 1977  OIL COM COM DIST. 3					
4-27-77 Layed down 2-7/8" tubing. Re-ran 2" tubing. Ran rods and put on pump.  MAY 6 1877  OIL CON COM DIST. 3  Les Controloal Suprey					
on pump.  MAY 6 1977  MAY 6 1977  OIL CON. COM. DIST. 3		and 3200 PSI.	and 3200 PSI.		
on pump.  MAY 6 1977  MAY 6 1977  OIL CON. COM. DIST. 3		Tanad Jana 2 7/01 a	notatora. De maio Official de	D =1	
MAY 6 1977  MAY 6 1977  OIL COM COM.  DIST. 3	4-21-11		tubing. ke-ran 2" tubing.	kan rods and put	
MAY 6 1977  MAY 6 1977  OIL COM. GOM.  DIST. 3		on pump.	The state of the s		
MAY 6 1977  MAY 6 1977  OIL COM. GOM.  DIST. 3				Recarding to the second	
MAY 6 1977  OIL COM. COM.  DIST. 3				TAME J BLUE DOWN	
MAY 6 1977  OIL COM. COM.  DIST. 3				MAY 5 1077	
			v a 1977	6 13/7	
			MAY		
	^	-	OIL COM COME	Et al Chucker Sharak	
18. I hereby certify that the foregoing is true and correct	./)		DIST: 3		
	18. I hereby certify that the	e foregoing is true and correct			