LINITED STATES

ONITED STATES	5. LEASE = 17.
DEPARTMENT OF THE INTERIOR	14-20-603-7106
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
	Navajo Tribe
CUMPRY NOTICES AND DEDORTS ON WELLS	7. UNIT AGREEMENT NAME
SUNDRY NOTICES AND REPORTS ON WELLS	
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)	8. FARM OR LEASE NAME
	Waterflow
1. oil XX gas other	9. WELL NO.
	3
2. NAME OF OPERATOR Crogory Merrion Of H	10. FIELD OR WILDCAT NAME
	So. Waterflow Gallup
3. ADDRESS OF OPERATOR P. O. Box 1017, Farmington, New Mexico 87499	
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	Sec. 20, T29N, 125W 2 3 3 2 3
below.) AT SURFACE: 1980' FSI, and 660 FWI.	12. COUNTY OR PARISH 13. STATE
	San Juan New Mexico:
AT TOTAL DEPTH	14. API NO. 3 5 5 5 5
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	14. AFI NO.
DEPORT OF OTHER DATA	4 ± 0 ½
REPORT, OR OTHER DATA	ELEVATIONS (SHOW DF, KDB, AND WD)
REQUEST FOR APPROVAL TO: TEST WATER SHUT-OFF TEST WATER SHUT-OFF	60 7 0 F 0 7 0 0
TEST WATER SHUT-OFF	AGG A SEES A FREE
FRACTURE TREAT	
SHOOT OR ACIDIZE	RVEY SEGUE SEGUES
REPAIR WELL	Report results of multiple completion or zone
PULL OR ALTER CASING	change on Form 9–330.)
MULTIPLE COMPLETE CHANGE ZONES CHANGE ZONES	
CHANGE ZONES UNAR O	ကြာသောလည်း 💹 ဆေးပြုပြု မေး ခွဲခွဲခဲ့ပါ 🔾
(other)	
Outlier y	V NA YERR E SERE
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clear including estimated date of starting any proposed work. If well is	e all pervised details, and give pertinent dates,
including estimated date of starting any proposed work. If well 19 a measured and true vertical depths for all markers and zones pertine	nt to this work.)*
Incasured and trac vertical deptils for an markets and zones permis-	무취실하다 전 기를 다
	క కొన్నాయి. ఈ ఉద్యే
Propose to plug and abandon as follows:	
	9 from 4221 1 1 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2
1. Place 12 sx (14.16 cu. ft.) plu	
2. Take free point and shoot off	casing. Place plug inside stub

- 50 and 50 ft. above stub.

 3. Place plug from 930' to 800' to cover Mesaverde.
- Place plug from 250' to surface.
 Erect dry hole marker.
- Place plug from 250' to surface.
 Erect dry hole marker.
 Reclaim surface per instructions of appropriate surface management agency.

	Setton
Subsurface Safety Valve: Manu. and Type	
18. I hereby certify that the foregoing is true and correct	
SIGNED TITLE Operations Manager DATE	3/1/83
(This space for Federal or State office use)	
APPROVED BY DATE	
CONDITIONS OF SAFFROVAL, PIF SANY:	
MEAR 07 1983	
JAMES F. SIM *See Instructions on Reverse Side	·
DISTRICT ENGINEER	

1380 FSL & 640 FWL SZO, 29N, 15W 85/8" @ 206' ω/135 5 x (circ) SAN JUAN, N.M.

> ELEU. 2 5372 G.L. 5384 K.B.

TOC @ 3900

GALLUP - 4183 - 4221

PBTD @ 4240 41/2" 95#@ 4266 w/1355X