

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 1004-0135
Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☐ GAS WELL ☐ OTHER ☒ Injection	7. UNIT AGREEMENT NAME Aztec Turb (term)
2. NAME OF OPERATOR Paramount Pet. Corp 40 BLM FDO	8. FARM OR LEASE NAME Aztec Turb UNIT (WI)
3. ADDRESS OF OPERATOR 1235 La Plata Hwy. Farmington NM 87401	9. WELL NO. 14
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 2130 15 & 3450 1E	10. FIELD AND POOL, OR WILDCAT Turb Gallup
14. PERMIT NO.	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA 19-29N-13W
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 5358 KB	12. COUNTY OR PARISH San Juan
	13. STATE NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐	PULL OR ALTER CASING ☐
FRACTURE TREAT ☐	MULTIPLE COMPLETION ☐
SHOOT OR ACIDIZE ☐	ABANDON* ☒
REPAIR WELL ☐	CHANGE PLANS ☐
(Other) ☐	

WATER SHUT-OFF ☐	REPAIRING WELL ☐
FRACTURE TREATMENT ☐	ALTERING CASING ☐
SHOOTING OR ACIDIZING ☐	ABANDONMENT* ☐
(Other) ☐	

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated dates of completion, and proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all completions and zones pertinent to this work.)*

Plan to plug well as follows:

- 1) POOH with tubing and packer, inspected.
Set plug from 5116 - 4686
- 2) Perit @ 2635 and plug inside & outside 4 1/2" casing
from 2635 - 2535 + 100% excess
- 3) Perit @ 2260 and plug inside & outside 4 1/2" casing
from 2260 - 2160 + 100% excess
- 4) Plug from 1183 - 1083 + 50% excess
- 5) Plug from 950 - 850 + 50% excess
- 6) plug inside & outside 4 1/2" casing from 400 to surface

RECEIVED
JAN 20 1993
OIL CON. DIV
DIST. 3

18. I hereby certify that the foregoing is true and correct

SIGNED Per Federal Contract 1422-N651-C2-2094

TITLE

DATE 1/15/93

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

NMOC

*See Instructions on Reverse Side

APPROVED

JAN 15 1993

AREA MANAGER