

- 2 - OCC Aztec ✓  
1 - Houston  
1 - Midland  
1 - Durango  
1 - File

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-122

Revised 12-1-55

MULTI-POINT BACK PRESSURE TEST FOR GAS WELLS

Pool Basin Dakota Formation Dakota County San Juan  
Initial X Annual \_\_\_\_\_ Special \_\_\_\_\_ Date of Test 10-8-61  
Company Tidewater Oil Company Lease Mae Gale, Et al Well No. 1  
Unit E Sec. 24 Twp. 29N Rge. 11W Purchaser El Paso Nat. Gas Co.  
Casing 4-1/2 Wt. 11.6 I.D. 4.000 Set at 6425 Perf. 6148 To 6158  
Tubing 2-3/8 Wt. 4.7 I.D. 1.995 Set at 6232 Perf. 6220 To 6280  
Gas Pay: From 6118 To 6288 L \_\_\_\_\_ xG \_\_\_\_\_ -GL \_\_\_\_\_ Bar.Press. \_\_\_\_\_  
Producing Thru: Casing \_\_\_\_\_ Tubing X Type Well Single Bradenhead  
Date of Completion: 9-7-61 Packer None Reservoir Temp. \_\_\_\_\_

OBSERVED DATA

Tested Through (Packer) (Choke) (Valve) Type Taps \_\_\_\_\_

Flow Data						Tubing Data		Casing Data		Duration of Flow Hr.
No.	(Prover) (Line) Size	(Choke) (Orifice) Size	Press. psig	Diff. h <sub>w</sub>	Temp. °F.	Press. psig	Temp. °F.	Press. psig	Temp. °F.	
SI										
1.	2"	3/4 TC	435			2053		2066		8 days B.I.
2.						435		971		3 hr.
3.										
4.										
5.										

FLOW CALCULATIONS

No.	Coefficient (24-Hour)	$\sqrt{h_{wpf}}$	Pressure psia	Flow Temp. Factor F <sub>t</sub>	Gravity Factor F <sub>g</sub>	Compress. Factor F <sub>pv</sub>	Rate of Flow Q-MCFPD @ 15.025 psia
1.	12.3650		447	0.9981	0.9608	1.047	5.550
2.							
3.							
4.							
5.							

PRESSURE CALCULATIONS

Gas Liquid Hydrocarbon Ratio \_\_\_\_\_ cf/bbl.  
Gravity of Liquid Hydrocarbons \_\_\_\_\_ deg.  
F<sub>c</sub> \_\_\_\_\_ (1-e<sup>-s</sup>)  
Specific Gravity Separator Gas \_\_\_\_\_  
Specific Gravity Flowing Fluid \_\_\_\_\_  
P<sub>c</sub> 2,078.0 P<sub>c</sub> 5,418,084

No.	P <sub>w</sub> P <sub>t</sub> (psia)	P <sub>t</sub> <sup>2</sup>	F <sub>c</sub> Q	(F <sub>c</sub> Q) <sup>2</sup>	(F <sub>c</sub> Q) <sup>2</sup> (1-e <sup>-s</sup> )	P <sub>w</sub> <sup>2</sup>	P <sub>c</sub> <sup>2</sup> -P <sub>w</sub> <sup>2</sup>	Cal. P <sub>w</sub>	P <sub>w</sub> P <sub>c</sub>
1.						966,289	3,351,795		0.47305
2.									
3.									
4.									
5.									

Absolute Potential: 6.711 MCFPD; n 0.75  
COMPANY Tidewater Oil Company  
ADDRESS Box 547, Hobbs, N. Mex.  
AGENT and TITLE Thomas E. Weaver, Area Supt.  
WITNESSED \_\_\_\_\_  
COMPANY \_\_\_\_\_

REMARKS



## INSTRUCTIONS

This form is to be used for reporting multi-point back pressure tests on gas wells in the State, except those on which special orders are applicable. Three copies of this form and the back pressure curve shall be filed with the Commission at Box 871, Santa Fe.

The log log paper used for plotting the back pressure curve shall be of at least three inch cycles.

## NOMENCLATURE

- $Q$  = Actual rate of flow at end of flow period at W. H. working pressure ( $P_w$ ).  
MCF/da. @ 15.025 psia and 60° F.
- $P_c$  = 72 hour wellhead shut-in casing (or tubing) pressure whichever is greater.  
psia
- $P_w$  = Static wellhead working pressure as determined at the end of flow period.  
(Casing if flowing thru tubing, tubing if flowing thru casing.) psia
- $P_t$  = Flowing wellhead pressure (tubing if flowing through tubing, casing if  
flowing through casing.) psia
- $P_f$  = Meter pressure, psia.
- $h_w$  = Differential meter pressure, inches water.
- $F_g$  = Gravity correction factor.
- $F_t$  = Flowing temperature correction factor.
- $F_{pv}$  = Supercompressability factor.
- $n$  = Slope of back pressure curve.

Note: If  $P_w$  cannot be taken because of manner of completion or condition of well, then  $P_w$  must be calculated by adding the pressure drop due to friction within the flow string to  $P_t$ .