Form 3160-5 (June 1990)

UNITED STATES

SECTION STATE

FORM APPROVED

DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT	Budget Bureau No. 1004-0135 Expires: March 31, 1993
SUNDRY NOTICES AND REPORTS ON WELLSUL 10 PM 1:58 Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals PANINGTON, NM	5. Lease Designation and Serial No. 14-20-603-2199 6. If Indian, Allottee or Tribe Name Navajo Nation
SUBMIT IN TRIPLICATE	7. If Unit or CA, Agreement Designation
1. Type of Well Oil Gas Well X Other WIW 2. Name of Operator	NW Cha Cha Unit 8. Well Name and No.
MOUNTAIN STATES PETROLEUM CORP. 3. Address and Telephone No.	NW Cha Cha Unit 16 9. API Well No.
P O BOX 3531, MIDLAND, TX 79702 915/685-0878 4. Location of Well (Footage, Sec., T., R., M., or Survey Description)	30-045-08068 10. Field and Pool, or Exploratory Area Cha Cha Gallup
1830' FNL & 660' FWL Sec. 22, T29N, R14W, NMPM	11. County or Parish, State San Juan, NM
CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPOR	T, OR OTHER DATA
TYPE OF SUBMISSION BY TYPE OF ACTION Notice of Intent Notice of Intent Subsequent Report Final Abandonment Office of Intent Notice o	Change of Plans New Construction Non-Routine Fracturing Water Shut-Off Conversion to Injection Dispose Water (Note: Report results of multiple completion on Well
3. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* 1. MT CRIL 2011 1 in Section 200 0.7.	Completion or Recompletion Report and Log form) any proposed work. If well is directionally drilled,
1) MI&RU pulling unit 6-30-97.	

- 2) Tried to set 4-1/2" cement retainer at 2246, unable to set retainer. RIH w/wireline, cut 2-3/8" tubing at 2196'. POH w/tubing.
- 3) RIH. Perforate casing at 2190'. Bullhead 75 sx cement into perf at 2190'. Cement Class H Neat with slurry wt 15.6. Tagged top of cement at 2079'.
- 4) Perforated 4-1/2" casing at 772'. Circulated 375 sx cement inside and outside 4-1/2" casing 772' to surface. Cement Class H Neat with slurry wt 15.6.
- 5) Cut off wellhead. Installed dry hole marker 4' below ground level. WELL PLUGGED & ABANDONED 7-7-97.

14. I hereby certify that the foregoing is true and correct		
Stand Lichelle was	Title Agent	Date 7-8-97
This space for Federal or State office use		
Approved by Sapproval, if any:	Title OR STORY	Date

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements