

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Revised 1-1-89

DISTRICT I

P.O. Box 1980, Hobbs, NM 88240

DISTRICT II

P.O. Drawer DD, Artesia, NM 88210

DISTRICT III

1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P.O. Box 2088

Santa Fe, New Mexico 87504-2088

WELL API NO.	3004508104
5. Indicate Type of Lease	STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No.	
7. Lease Name or Unit Agreement Name	Martinez Gas Com D
8. Well No.	#1
9. Pool name or Wildcat	Aztec Pictured Cliffs

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	
1. Type of Well: OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER	
2. Name of Operator AMOCO PRODUCTION COMPANY	Attention Pat Archuleta
P.O. Box 800 Denver Colorado 80201 303-830-5217	
4. Well Location Unit Letter B : 1130 Feet From The NORTH Line and 1780 Feet From The EAST Line Section 24 Township 29N Range 10W NMPM SAN JUAN County	
10. Elevation (Show whether DF, RKB, RT, GR, etc.)	

11. Check Appropriate Box to Indicate Nature of Notice Report or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
OTHER: <input type="checkbox"/>	PLUG AND ABANDONMENT <input checked="" type="checkbox"/>
	CASING TEST AND CEMENT JOB <input type="checkbox"/>
	OTHER: <input type="checkbox"/>

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

MIRUSU 3/21/97.

Set CIBP at 1900', load and test csg to 500#. Held okay.

Spot sement plug inside csg from 1900'-1500' w/53sxs CI-B cement. Shoot squeeze hole at 868' attempt to into holes could not. TOH

Spot cement plug from 1025' across perms at 868' to 700' w/38 sxs CI-B cement.

Spot cement plug inside csg form 350' to surface w/43 sxs CI-B cement.

Cut off wellhead and top off csg to surface, install marker

RDMSOU 3/24/97.

RECEIVED
APR - 9 1997

OIL CON. DIV.
DIST. 3

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Pat Archuleta TITLE Staff Assistant DATE 04-04-1997

TYPE OR PRINT NAME Pat Archuleta TELEPHONE NO. 303-830-5217

(This space for State)

APPROVED BY James Carlson TITLE Deputy O&G Inspector DATE 5-8-97

CONDITIONS OF APPROVAL, IF ANY: