Form 9–331 Dec. 1973	Form Approved. Budget Bureau No. 42–R1424
UNITED STATES	5. LEASE
DEPARTMENT OF THE INTERIOR	SF 078266
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
SUNDRY NOTICES AND REPORTS ON WELLS	7. UNIT AGREEMENT NAME
(Do not use this form for proposals to drill or to deepen or plug back to a difference reservoir. Use Form 9–331–C for such proposals.)	8. FARM OR LEASE NAME
1. oil gas other	San Jacinto 9. WELL NO.
2. NAME OF OPERATOR	#4
El Paso Natural Gas Company	10. FIELD OR WILDCAT NAME
3. ADDRESS OF OPERATOR	Aztec Pictured Cliffs
P.O. Box 289 Farmington, New Mexico 87401 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 1	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
below.)	Sec. 21, T-29-N, R-10-W
AT SURFACE: NW/4 NE/4 AT TOP PROD. INTERVAL:	12. COUNTY OR PARISH 13. STATE
AT TOTAL DEPTH:	San Juan New Mexico
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE	
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD)
· ·	5617 GR
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	
FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL PULL OR ALTER CASING MULTIPLE COMPLETE CHANGE ZONES ABANDON* (other) RECE FEB 05 U. S. GEOLOGIC FARMINGTO	(NOTE: Report results of multiple completion or zone change on Form 9–330.) CAL SURVEY
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly st including estimated date of starting any proposed work. If well is measured and true vertical depths for all markers and zones pertin	rate all pertinent details, and give pertinent dates, directionally drilled, give subsurface locations and tent to this work.)*
It is planned to P. & A. this well in the fo	
1) Pick up on 1-1/4" tubing to see if it is	stuck.
2) Circulate hole clean of drip etc. w/ 9.2	
3) Spot 50' bottom plug on top of bridge plu4) Pull up and spot 100' plug across Fruitla	
5) POOH & perf @ 950' and @ 151'.	and (1010 -1/ 2 0).
6) Go in with 2" work string and squeeze 75 Ojo Alamo & Kirtland, 740' to 950'.	sks @ 950' to cover outside of
7) Spot 210' plug from 740' to 950' (50' above 151' 8) Pull up and squeeze 45 sacks at 151' to s	ve & below Ojo Alamo and Kirtland).
surface casing.	ourrace to the 3-1/2 lifto 0-3/8"
9) Spot 100' plug 51' to 151'. Inside surfa	ace string tie in.
10) Spot 50' surface plug and install DHM.	
Subsurface Safety Valve: Manu. and Type	Set @ Ft.
18. I hereby certify that the foregoing is true and correct Product:	ion
	r DATE February 1, 1982
APPROVED ace for Federal or State	
CONDITIONS OF APPROVAL HIBANY: 1 1982	DATE

en de la composition La composition de la La composition de la La composition de la composition della composition della

الإستينيون المال المال je je terika e t e o samana naveje.

> DISTRICT ENGINEER See Instructions on Reverse Side

ForJAMES F. SIMS

NMOCC