Form	9-331
(May	1963)

16.

UNITED STATES

SUBMIT	IN	TRIPL	CA?	re•
(Other 1		uctions	on	re-
verse side				


Form approved. Budget Bureau No. 42-R1424.

	ENT OF THE INTERIOR (Other Instructions on reconstructions of reconstructions on reconstructions on reconstructions on reconstructions on reconstructions of reconstructions on reconstructions of reconstructions on reconstructions on reconstructions on reconstructions on reconstructions on reconstructions on reconstructions of reconstr	5. LEASE DESIGNATION A 14-20-603-21 6. IF INDIAN, ALLOTTEE	98
	IS AND REPORTS ON WELLS Is to drill or to deepen or plug back to a different reservoir.	Navajo Tribe	
OIL GAS WELL OTHER 2. NAME OF OPERATOR J. Gregory Merrion and 3. ADDRESS OF OPERATOR P.O. Box 507, Farmington and the second of well (Report location clesses also space 17 below.) At surface		8. FARM OR LEASE NAME Navajo H 9. WELL NO. 4 10. FIELD AND POOL, OR West Kutz	WILDCAT
510 FNL and 2130 FWL 14. PERMIT NO.	15. ELEVATIONS (Show whether DF, RT, GR, etc.) 5356 ft. K.B.	Sec. 24, T29 12. COUNTY OR PARISH San Juan	N, R14W

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT NEIGHT OF		
TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL	PULL OR ALTER CASING MULTIPLE COMPLETE ABANDON* CHANGE PLANS		WATER SHUT-OFF FRACTURE TREATMENT SHOOTING OR ACIDIZING (Other) (NOTE: Report results of mu Completion or Recompletion	REPAIRING WELL ALTERING CASING ABANDONMENT* Iltiple completion on Well Report and Log form.)

- 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *
 - Rig up Blue Jet and ran Gamma Ray Neutron Correlation Log and Cement Bond Log. Top of cement at 778' KB. Perforated Picture Cliff 982-92 ft. K.B. with 1 PF 2-1/8" glass jets. Rig up Dowell and fraced with 2520 gallons of diesel, 10,000 lbs. sand, 160 bbls. KCL water. Perforated the Fruitland 842-82 ft. K.B. with 1 P/2 ft. with 2-1/8" glass jets. Fraced with 1000 lb. 10/20 sand, 10,000 lb. 20/40 sand, and 326 bbls. KCL water.
 - No production indicated, 7-16-77 Rig up Nowsco and blow well with nitrogen. preparing to abandon.



(This space for Federal or State office use)

18. I hereby certify that the foregoing is true and correct

APPROVED BY CONDITIONS OF APPROVAL, IF ANY: TITLE

Engineer

DATE FECEIVED

NOV 15 1977