

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ gas ☐
well well other

2. NAME OF OPERATOR
~~J. Gregory Morrison~~ *Morrison Drilling*

3. ADDRESS OF OPERATOR
P. O. Box 1017, Farmington, New Mexico 87499

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 660' FNL and 1980' FEL

AT TOP PROD. INTERVAL: Same

AT TOTAL DEPTH: Same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON* ☒

(other) ☐

SUBSEQUENT REPORT OF:

RECEIVED
MAR 2 1983

U. S. GEOLOGICAL SURVEY
FARMINGTON, N. M.

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

OIL CON. DIV.
DIST. 9

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Propose to plug and abandon as follows:

1. Place 15 sx (17.70 cu. ft.) plug from 4253 - 4100' to cover Gallup perfs.
2. Take free point and shoot off casing. Place plug 50 ft. inside of stub and 50 ft. above stub.
3. Pull casing and place plug across Cliffhouse and 100 ft. above, from 950' - 800'.
4. Place surface plug from 260' to surface.
5. Erect dry hole marker.
6. Reclaim surface per instructions of appropriate surface management agency.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED *[Signature]* TITLE Operations Manager DATE 3/1/83

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL IF ANY:

APPROVED
MAR 07 1983
[Signature]
JAMES F. SIMS
DISTRICT ENGINEER

*See Instructions on Reverse Side

NMOCC

~~Wallylow~~
~~NAVAJO TRACT 12 #1.~~

WELLBORE DIAGRAM

- SURFACE FRUITLAND FORMATION

460 FNL ; 1980 FEL

S 19, 29N, 15W

SAN JUAN, N.M.

8 5/8" @ 212' w/ 150 SX (CIRC) ELEV. 5428' C.L.

5441' K.B

TOC @ 2002' (CALCULATED)

HOLE @ 2572' CIRCULATED OUT BRADEN HEAD
AND SQUEEZED w/ 110 SX CLASS 6

EST. TOP @ 3946' (CALCULATE)

GALLUP - 4213-20

4230-53

PBTD @ 4318'

4 1/2" 9.5# @ 4364 w 100 SX 50-50 POZ 2% GA