



STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT
OIL CONSERVATION DIVISION
AZTEC DISTRICT OFFICE

TONEY ANAYA
GOVERNOR

1000 RIO BRAZOS ROAD
AZTEC, NEW MEXICO 87410
(505) 334-6178

DIVISION APPROVED PLUGGING PROGRAM

Farmington Syndicate
Blake #1
O-16-29N-13W
San Juan County, N.M.

Presumed Downhole Equipment

8" @ 1100' presumed pulled prior to running 6 5/8"
6 5/8" @ 2400'.

Cementing history is not known.

1. Clean out hole/or drill out to 2400'.
2. Set a cement plug inside and outside casing from T.D.- 2300' to isolate the Cliff House formation.
3. Set a cement plug inside and outside casing from 1100' - 900' to isolate Pictured Cliffs formation.
4. Set a cement plug inside and outside casing from 400' - surface to isolate Farmington S.S. formation.
5. Set dry hole marker.
6. Clean and restore location to original condition.
7. All plugs shall be of Class A, B, or C neat cement and may be accelerated by up to 3% CaCl_2 .
8. All plugs are to be separated by gel mud of minimum nine pounds per gallon.

Note: Casing may have been shot off at an unknown depth and pulled. If so, the plugging program will have to be revised.

DEPT. OF ENERGY	
OIL CONSERVATION DIVISION	
EXHIBIT NO.	7
CASE NO.	8490