



(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYLand Office **Santa Fe**
Lease No. **076958**
Unit **South Half**

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	SUBSEQUENT REPORT OF WATER SHUT-OFF.....
NOTICE OF INTENTION TO CHANGE PLANS.....	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....	SUBSEQUENT REPORT OF ALTERING CASING.....
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.....
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....	SUBSEQUENT REPORT OF ABANDONMENT.....
NOTICE OF INTENTION TO PULL OR ALTER CASING.....	SUPPLEMENTARY WELL HISTORY.....
NOTICE OF INTENTION TO ABANDON WELL.....	

RECEIVED
SEP 13 1962
U. S. GEOLOGICAL SURVEY
FARMINGTON, NEW MEXICO

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

September 13, 1962

J. Glenn Turner - Hare

Well No. 1-14 is located 925 ft. from N line and 1,630 ft. from W line of sec. 14SW/4 Section 14
(1/4 Sec. and Sec. No.)T 29-N R 10-W
(Twp.) (Range)N.M.P.M.
(Meridian)Basin Dakota
(Field)San Juan County
(County or Subdivision)New Mexico
(State or Territory)The elevation of the derrick floor above sea level is 5,663 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work.)

August 2, 1962. After drilling to 6,800 feet - ran 215 joints 4-1/2", 10.5# J-55 casing, landed at 6800'. Cemented stage 1 with 140 sacks 4% gel (14.1#/gal.) followed by 100 sacks .9% Latex cement (14.5#/gal.) Displaced with 108 barrels water. Bumped plug with 2,000 psi. Float held. Stage collar at 2192'. Cemented stage 2 with 100 sacks 4% gel. cement (14.1#/gal.). Displaced with 35 barrels water. Closed stage collar with 2,500 psi. Had complete returns.

August 24, 1962. Tested casing with 3,500 psi. Found no leaks. Ran PGAC cement bond log. Log showed good bond throughout with top of cement at 5860'. Perforated stage 1: 4 jet shots/ft. 6474'-6479'; 6494'-6499'; 6529'-6534'; 6591'-6596'. Sand Fractured Stage 1 with 80,000# 20-40 sand; 80,000 gal. water with 1% CaCl 2 & 10# J-2/1000 gal. water. Dropped 20 ballscalears after 45,000# sand.

8/25/62. Ran 206 jts. 2-3/8", 4.7# J-55 tubing. Landed at 6528'. Shut well in.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company J. Glenn TurnerAddress P. O. Box 728Farmington, New Mexico

By C. Beeson Neal
Title Agent in Farmington

RECEIVED
SEP 14 1962
GEOLOGICAL SURVEY
FARMINGTON, N.M.