

DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

(Other instructions on reverse side)

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER		6. LEASE DESIGNATION AND SERIAL NO. SF-077710	
2. NAME OF OPERATOR R & G DRILLING CO.		7. IF INDIAN, ALLOTTEE OR TRIBE NAME	
3. ADDRESS OF OPERATOR c/o Walsh Engineering & Prod. Corp. P. O. Box 254, Farmington, New Mexico 87401		7. UNIT AGREEMENT NAME	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 1850'FSL, 1780'FWL		8. FARM OR LEASE NAME Hardie	
14. PERMIT NO.		9. WELL NO. 2	
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 5666' GL		10. FIELD AND POOL, OR WILDCAT Fulcher Kutz P. C.	
		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 14-T29N-R12W N.M.P.M.	
		12. COUNTY OR PARISH San Juan	
		13. STATE New Mex.	

## 16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

## NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
(Other) ☐

PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
ABANDON\* ☐  
CHANGE PLANS ☐

## SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐  
FRACTURE TREATMENT ☐  
SHOOTING OR ACIDIZING ☐  
(Other) ☐

REPAIRING WELL ☐  
ALTERING CASING ☐  
ABANDONMENT\* ☒

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

2-26-77

This well was plugged and abandoned in the following manner:

1. Set 35 sack cement plug 1600'-1711'.
2. Perforate 4 holes at 600'. Set 65 sack cement plug in and out of casing 400' to 600'.
3. Set 5 sack surface plug with dry hole marker.



APR 14 1977  
U. S. GEOLOGICAL SURVEY

For: R &amp; G Drilling Co.

18. I hereby certify that the foregoing is true and correct

SIGNED

Ewell N. Walsh, P. E.

TITLE

President, Walsh Engineering &amp; Production Corp.

DATE

4/13/77

(This space for Federal or State office use)

APPROVED

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

JUN 8 1978

E. I. McGRATH

DISTRICT ENGINEER

\*See Instructions on Reverse Side