


(SUBMIT IN TRIPLICATE)

Indian Agency Navajo



UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Allottee

Lease No. 24-20-0602-6377

CONFIDENTIAL
SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	<input checked="" type="checkbox"/>
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO REDRILL OR REPAIR WELL	SUBSEQUENT REPORT OF REDRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY	<input checked="" type="checkbox"/>
NOTICE OF INTENTION TO ABANDON WELL		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

March 25, 1964

Navajo Tract 2A

Well No. 1 is located 2060 ft. from [S] line and 1990 ft. from [E] line of sec. 18

NW 34 Section 18

(1/4 Sec. and Sec. No.)

29N

(Twp.)

15W

(Range)

RM1PM

(Meridian)

South Waterflow

(Field)

San Juan

(County or Subdivision)

New Mexico

(State or Territory)

The elevation of the derrick floor above sea level is - ft. **5387' Ground Level Ungraded**

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Spudded 1-13-64. TD 4265', PRTD 4238'. Set 6-jts. 8-5/8" casing @ 209', cemented w/125 cu. Set 13-jts. 4 1/2" casing @ 4265', cemented w/125 cu. Perf. 4208' & 4209', spotted 200 gals. MCA, acidized w/500 gal. MCA. Swab 31 bls. fluid, 99% water. Squashed perf. 4208-09'. Perf. 4193-94-95', spotted w/200 gals. MCA. Swab 16 bls. load oil, 5 bls. acid water, 5 bls. new oil & 7 bls. water. Set ret. bridge plug @ 4190'. Perf. 4177', 4179' & 4181', soaked 200 gals. MCA at 500 lbs. Swab 4 hrs., rec. 8 b.o. & 19 b.w. Pulled ret. R.P., tested, found communication between top & middle zones. Perf. 4178', 4180', 4182', 4196', 4197' & 4198'. Old perf. 4177', 4179', 4181', 4193', 4194' & 4195'. Free, spearhead 5000 gal. crude followed by 20,000 gal. crude & 20,000 lbs. sand and 400 lbs. parashok. Flowed 24 hours, rec. 153 bls. load oil. 613 bls. to recover. Pump Testing. Completed 3-23-64 as an oil well, pumping 20 bls. oil & 76 bls. water.

I understand that this plan of work must receive approval in writing by the Geological Survey before operation may be commenced.

Company Humble Oil & Refining Company

Address P. O. Box 3082

Durango, Colorado

By **COPY (ORIGINAL SIGNED) B. H. BRADLEY**

Title Dist. Supt.

