Form 9-331 b (April 1952)						

(SUBMIT IN TRIPLICATE)

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

Indian Agency	Ni. Y	*JE) -	(
Allettee SHEL	<u> </u>			
Lease No.14 20				3

		s_		ļ	
NOTICE OF INTENTION TO DRILL		I II	QUENT REPORT OF WATER SHUT-OFF	1	
		1 1	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING		
NOTICE OF INTENTION TO TEST WATER SHUT-OFF		1 1	SUBSEQUENT REPORT OF ALTERING CASING		
notice of intention to redrice or r notice of intention to shoot or aci		1 1	QUENT REPORT OF ABANDONMENT.	1	
NOTICE OF INTENTION TO SHOOT OR ACT		1 11	EMENTARY WELL HISTORY	100	
NOTICE OF INTENTION TO ABANDON WEL					
(INDICATE AS	BOVE BY CHECK MARI	K NATURE OF I	REPORT, NOTICE, OR OTHER DATA)		
CALL MAN IN THE PARTY OF THE PARTY.		~~~~~~~	<u> 5 6 61</u>	, 19_	
SHIPROCK 17	13080 G C	XXX 1	3275 a c 238 h	ne of sec17	
vell No. <u>J-8</u> is locate	ed 4.399 t. 11	rom [S] III	le and Ext. It. Irom said in	ie of sec	
HU RE	29N	10%	WPK		
(14 Sec. and Sec. No.)	(Twp.)	(Range)	(Meridian)		
shiprock sa llup	san Jus	y or Subdivision	New Mexico (State or Te		
tate names or and expected depths to ob	ing points, and all	izes, weights, a l other import	and lengths of proposed casings; indicate ant proposed work)	mudding jobs, cet	
Drilled 6 3/4 hole	to 64'	and set	and lengths of proposed casings; indicate ant proposed work) 66 of 51 Casing 5 sam. Orilled 4	on Texas	
Drilled 6 3/4 hole Shoe and cemented	to 64'	and set	66' of 5%" Casing	on Texas	
Drilled 6 3/4 hole	to 64'	and set	66' of 5%" Casing	on Texas	
Drilled 6 3/4 hole Shoe and cemented	to 64'	and set	66' of 5%" Casing	on Texas	
Drilled 6 3/4 hole Shoe and cemented	to 64'	and set	66' of 5%" Casing 5 sam. Orilled 4	on Texas	
Drilled 6 3/4 hole Shoe and cemented	to 64'	and set	66' of 5%" Casing	on Texas	
Drilled 6 3/4 hole Shoe and cemented	to 64'	and set	66' of 5%" Casing 5 sam. Orilled 4	on Texas	
Drilled 6 3/4 hole Shoe and cemented to 84' TD.	to 64°	and set	RECEIVE	on Texas 3/4 hole	
Drilled 6 3/4 hole Shoe and cemented to 84' TD.	to 64°	and set	66' of 5%" Casing 5 sam. Orilled 4	on Texas 3/4 hole	
Drilled 6 3/4 hole shoe and comented to 84' TD.	to 64°	and set	RECEIVE	on Texas 3/4 hole	
Drilled 6 3/4 hole shoe and cemented to 84' TD.	to 64°	and set	REFIVE MAY 1 0 19 OIL The Geological Survey before operations	on Texas 3/4 hole	
Drilled 6 3/4 hole Shoe and cemented to 34' TD. I understand that this plan of work me	to 64°	and set	66' of 5%" Casing San. Orilled 4 RECEIVE MAY 1 0 19 OIL DIST The Geological Survey before operations	on Texas 3/4 hole	
Drilled 6 3/4 hole Shoe and comented to 84. TD. I understand that this plan of work many Company ROYAL DEVE	to 64°	and set	66' of 5%" Casing San. Orilled 4 RECEIVE MAY 1 0 19 OIL DIST The Geological Survey before operations	on Texas 3/4 hole	
Drilled 6 3/4 hole Shoe and comented to 84' TD. I understand that this plan of work me	to 64°	and set	REFIVE MAY 1 0 19 OIL The Geological Survey before operations	on Texas 3/4 hole	
Drilled 6 3/4 hole Shoe and cemented to 84. TD.	to 64°	and set	66' of 5%" Casing San. Orilled 4 RECEIVE MAY 1 0 19 OIL DIST The Geological Survey before operations	on Texa 3/4 hol	