



(SUBMIT IN TRIPLICATE)

**UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY**

Land Office Santa Fe  
 Lease No. 079509  
 Unit N/2

## SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF	XXXX
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	XXXX
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

December 2, 1962

J. Glenn Turner - Owner  
 Well No. 2-14 is located 1,760 ft. from [N] line and 1,480 ft. from [E] line of sec. 14

NE/4 Section 14      T 29-N R 10-W      N.M.P.M.  
 (1/4 Sec. and Sec. No.)      (Twp.)      (Range)      (Meridian)  
Basin Dakota      San Juan County      New Mexico  
 (Field)      (County or Subdivision)      (State or Territory)

The elevation of the derrick floor above sea level is 5,904 ft.

### DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudlogging jobs, cementing points, and all other important proposed work)

10/5/62 - After drilling to 6,958 feet - ran 214 joints 4-1/2", 10.5#, J-55 STC Casing - total string 6,967.68' - landed at 6,958'. Cemented stage 1 with 270 sacks w/4% gal @ 14.1#/gal. Displaced cement with 100 BW. Bumped plug with 2000 psi. Float held. Stage collar at 2,416' RKB. Cemented Stage 2 with 100 sacks w/4% gal @ 14.1#/gal. Displaced cement with 39 BW. Closed stage collar with 2500 psi.

10/13/62. Cleaned out to PBTD of 6910'. Pressure tested casing with 3500 psi. No leaks. Perforated: 4 jet shots/ft: Intervals: 6685' 6690'; 6756' 6761'. Fractured with 80,000# 20-40 sand, 80,000 gal. water w/1% CaCl<sub>2</sub> and 24# WAC-8/1000 gal. Dropped 20 balls at end of 40,000 gal. BDP 2300 psi. Average rate 37.2 BPM @ 2600 psi.

(Continued on separate page)

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company J. Glenn Turner  
 Address P.O. Box 728  
Farmington, New Mexico

By C. Beeson Neal  
 Title C. Beeson Neal, Agent in Farmington