

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPLICATE*
(Other instructions on reverse side)

Form approved.
Budget Bureau No. 1004-()
Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. **Depleted** Reference 14-20-603-5036
WELL ☒ GAS WELL ☐ OTHER 3162.3-4 (016)
2. NAME OF OPERATOR

3. ADDRESS OF OPERATOR Texas Eastern Developments, Inc.

4. P. O. Box 2521 Houston, TX 77252-2521
LOCATION OF WELL (Report location clearly and in accordance with any state requirements.
See also space 17 below.)
At surface

2267' FSL & 430' FEL

APR 10 1987

14. PERMIT NO. 15. ELEVATIONS (Show whether at top of casing, etc.)
5201.93 GR.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐ PULL OR ALTER CASING ☐
FRACTURE TREAT ☐ MULTIPLE COMPLETE ☐
SHOOT OR ACIDIZE ☐ ABANDON* ☐
REPAIR WELL ☐ CHANGE PLANS ☐
(Other) ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐ REPAIRING WELL ☐
FRACTURE TREATMENT ☐ ALTERING CASING ☐
SHOOTING OR ACIDIZING ☐ ABANDONMENT* ☒
(Other) ☐

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Well Data

Spud 3/14/61 TD 115' Hole Size 7" Casing 5 1/2" @ 85' cmt'd w/ 5.0 sx.

Casing Recovered: Size Amount 0 ft.

Producing interval: 85' - 115'

Method of Plugging: Halliburton Pump

Type Cement: Portland w/8% Bentonite, slurry wt. 13.3 ppg, slurry vol. 1.82 cu ft/sx

Remove rods, pump and tubing.

1st stage cement: Squeeze 7.50 cu ft, set plug 115' to surface w/ 9.3 cu ft.

Top cement at 42'.

2nd stage cement: set plug 42' to surface w/ 5.60 cu ft cement.

Dates

Notice of intent to plug approved: JAN. 28, 1987

Well plugged: MARCH 13, 1987

Land Restoration: MARCH 25, 1987

Marker set: APRIL 2, 1987

Land seeded:

Approved as to plugging of the well and
Liability under bond in connection with
surface restoration is completed.

18. I hereby certify that the foregoing is true and correct

SIGNED H. N. Hinds

TITLE Drilling Superintendent

M. N. Hinds

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

TITLE

APPROVED

DATE
APR 15 1987

AREA MANAGER
FARMINGTON RESOURCE AREA

*See Instructions on Reverse Side

NMOC