



TONEY ANAYA  
GOVERNOR

STATE OF NEW MEXICO  
**ENERGY AND MINERALS DEPARTMENT**  
OIL CONSERVATION DIVISION  
AZTEC DISTRICT OFFICE

1000 RIO BRAZOS ROAD  
AZTEC, NEW MEXICO 87410  
(505) 334-6178

DIVISION APPROVED PLUGGING PROGRAM

Basin Company  
Ted White #78  
H-18-29N-13W  
San Juan County, N.M.

Presumed Down Hole Equipment

8 5/8" @ 99' with 50 sacks of cement  
5 1/2" @ 960' with 75 sacks of cement  
Hydramite plug set @ 990'-985'  
Cement fill inside casing to 959'

1. Install proper well head equipment.
2. Set a plug inside 5 1/2" casing from 959'-859'.
3. Set a plug inside and outside 5 1/2" casing from 400' - surface to isolate Farmington S.S.
4. Set ~~top plug and dry hole marker with a minimum of 10 sacks of cement.~~
5. Clean and restore location to original condition.
6. All plugs shall be of class A, B, or C neat cement and may be accelerated by up to 3% CaCl<sub>2</sub>.
7. All plugs are to be separated by gel mud of minimum nine pounds per gallon.

10

8491