٠.					
ļ					(3)
Ì					7, C)
					3
				L.	.*
Į	l	!	i	! !	

(SUBMIT IN TRIPLICATE)

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

Land Office Lease No.	-06	555	7-		
OIMC	(D)			-	 5

Went All

	CES AND REPORTS ON WELLS. GER. FARMEN	
NOTICE OF INTENTION TO DRILL		
OTICE OF INTENTION TO CHANGE PLANS		- 1
OTICE OF INTENTION TO TEST WATER SHUT-OFF		1
OTICE OF INTENTION TO RE-DRILL OR REPAIR WE		
OTICE OF INTENTION TO SHOOT OR ACIDIZE		ł
NOTICE OF INTENTION TO PULL OR ALTER CASING.	1)	
NOTICE OF INTENTION TO ABANDON WELL		
(INDICATE ABOVE BY C	CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)	
(INDICATE ABOVE BY C	THE WARR NATURE OF REPORT, NOTICE, ON OTHER DATA!	
		1953
ell No. 22 is located 2000	ft. from $\binom{N}{N}$ line and ft. from $\binom{N}{W}$ line of sec.	13
and Sec. No.)	M.M. (Boltan)	
eloker Majuta	(C. 188 or Subdivision)	
•		
	DETAILS OF WORK	
	nds; show sizes, weights, and lengths of proposed casings; indicate mudding job nts, and all other important proposed work)	
sing retary tools, set approx 3-3/h° hele, circulate comen' ele using med to top ef F.G.	the surface, test for unter shut-off. Drill point with 6-3/4" bit, ren and coment approximately approxim	ing : 18-j nal z. 19
sing retary tools, set approx 3-3/h hole, circulate comen ele using und to top of F.G. ore barrell. Heem to casing f lbf. J-55, 5-1/2" casing.	the surface, test for unter shut-off. Drill point with 6-3/4" bit, ren and coment approximately approxim	ing : 18-; nal K. 1
sing retary tools, set approx 3-3/h hele, circulate cement ele using und to top ef F.G. ore barrell. Heam to easing f lig, J-55, 5-1/2" casing. lean out to bettom and 1" twi	the surface, test for unter shut-off. Drill point with 6-3/4" bit, ren and coment approximately approxim	ing 1 8-1 8-1 8-1 8-1 8-1 8-1 8-1 8-1 8-1 8
sing retary tools, set approx 3-3/h hele, circulate cement ele using und to top ef F.G. ore barrell. Heam to easing f lig, J-55, 5-1/2" casing. lean out to bettom and 1" twi	ads; show sizes, weights, and lengths of proposed casings; indicate mudding job nts, and all other important proposed work) x. 120' of 32.75%, J-55, 10-3/4" surface case to surface, test for water shut-off. Drill mand. Core for top of P.C. using convention point with 8-3/4" bit, run and coment approx hove on cable tools, drill send, shoot with bing.	ing 1 8-1 8-1 8-1 8-1 8-1 8-1 8-1 8-1 8-1 8
sing retary tools, set approximate coments of maing and to top of F.G. ore barrell. Hean to easing f lbf, J-55, 5-1/2" casing. lean out to betten and 1" to	ads; show sizes, weights, and lengths of proposed casings; indicate mudding job nts, and all other important proposed work) x. 120' of 32.75%, J-55, 10-3/4" surface case to surface, test for water shut-off. Drill mand. Core for top of P.C. using convention point with 8-3/4" bit, run and coment approx hove on cable tools, drill send, shoot with bing.	ing 1 8-1 8-1 8-1 8-1 8-1 8-1 8-1 8-1 8-1 8
ring retary tools, set appropriate common ple using mad to top of F.C. are barrell. Heam to easing I lif. J-55, 5-1/2" casing. lean out to better and 1" two leans of the lean	ads; show sizes, weights, and lengths of proposed casings; indicate mudding job note, and all other important proposed work) 2. 120' of 32.75%, J-55, 10-3/4" surface cases to surface, test for unter shut-off. Drill rand. Core for top of P.C. using convention point with 8-3/4" bit, ran and coment approximate an cable tools, drill sand, shoot with bing. By D. W. B. D. W. B. D. W. B. D. W. B. B. B. D. W. B. B. D. W. B. B. B. D. W. B. B. D. W. B. B. D. W. B. B. B. B. D. W. B. B. B. B. D. W. B. B. B. B. B. B. B. B. B. D. W. B.	ing 1 8- mal z. 1 8. N
ring retary tools, set appropriate communication of the case of th	ads; show sizes, weights, and lengths of proposed casings; indicate mudding job note, and all other important proposed work) 2. 120' of 32.75%, J-55, 10-3/4" surface cases to surface, test for unter shut-off. Drill rand. Core for top of P.C. using convention point with 8-3/4" bit, ran and coment approximate an cable tools, drill sand, shoot with bing. By D. W. B. D. W. B. D. W. B. D. W. B. B. B. D. W. B. B. D. W. B. B. B. D. W. B. B. D. W. B. B. D. W. B. B. B. B. D. W. B. B. B. B. D. W. B. B. B. B. B. B. B. B. B. D. W. B.	ing 1 8- mal z. 1: 8.W

was the first of t

and the control of th

ease	Cas	rroll-Corr	nell W	Vell No11	·····
ec. 13	, T	29 N. , I	R 12 W.	N.M.P.M	- RECEIVE
tì	ne West li	ne.		1650' fro	MOV 2.5 (1.53) U. S. ETHER OTT M. SERVE
		raded Rive			ranny, garetty, 11. 22.
San Juan	County		New F	ext.co	7
	990'				
16.	50				
		ŀ			
		•••••			
		—(¹³)—			_
		Ť			
					- TILES
					"OFITIVED"
					DEC 1 153 OIL CON. COM
					OIL CON. CON
Scale—4 inch	es equal 1 mil	e.			OIL CONT. 3
of actual sur	vevs made by	me or under	my supervi	from field no sion and that edge and belief	the
	E	- Dines	V D.	Ech	Shout
Seal:		Register	red Profess	sional -	Ernest V. Echohawk N. Mex. Reg. No. 1