

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENTFORM APPROVED  
OMB NO. 1004-0135  
Expires: November 30, 2000

## SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to re-enter an abandoned well. Use form 3160-3 (APD) for such proposals.

5. Lease Serial No.

NMSF 03877

6. If Indian, Allottee or Tribe Name

7. If Unit or CA/Agreement, Name and/or No.

8. Well Name and No.  
FOGELSON 11

9. API Well No.

30-045-08440

10. Field and Pool, or Exploratory  
BASIN DAKOTA

11. County or Parish, and State

SAN JUAN COUNTY, NM

SUBMIT IN TRIPLICATE - Other instructions on reverse side

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other2. Name of Operator  
CONOCO INC.Contact: DEBORAH MARBERRY  
E-Mail: deborah.moore@usa.conoco.com

3a. Address

P.O. BOX 2197 DU 3066  
HOUSTON, TX 77252

3b. Phone No. (include area code)

Ph: 281.293.1006

Fx: 281.293.5466

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

Sec 11 T29N R11W SESE 890FSL 890FEL

## 12. CHECK APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION	TYPE OF ACTION			
<input checked="" type="checkbox"/> Notice of Intent	<input type="checkbox"/> Acidize	<input type="checkbox"/> Deepen	<input type="checkbox"/> Production (Start/Resume)	<input type="checkbox"/> Water Shut-Off
<input type="checkbox"/> Subsequent Report	<input type="checkbox"/> Alter Casing	<input type="checkbox"/> Fracture Treat	<input type="checkbox"/> Reclamation	<input type="checkbox"/> Well Integrity
<input type="checkbox"/> Final Abandonment Notice	<input type="checkbox"/> Casing Repair	<input type="checkbox"/> New Construction	<input type="checkbox"/> Recomplete	<input checked="" type="checkbox"/> Other Workover Operation
	<input type="checkbox"/> Change Plans	<input type="checkbox"/> Plug and Abandon	<input type="checkbox"/> Temporarily Abandon	
	<input type="checkbox"/> Convert to Injection	<input type="checkbox"/> Plug Back	<input type="checkbox"/> Water Disposal	

13. Describe Proposed or Completed Operation (clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recompleat horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports shall be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompleat in a new interval, a Form 3160-4 shall be filed once testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the site is ready for final inspection.)

Conoco proposes to slimhole this well using the following procedure:

1) Hold safety at muster point, determine prevailing wind direction for that location, review procedure and identify potential hazards, isolate surface facilities, bleed off lines, lock out tag out, spot equipment, rig up, WORK SAFELY!

2) Pull tubing string and packer (laying down (packer type, listed as Halliburton R-4 run in 1996. Tubing String & #6211; 2.375" & #8221; 4.7#, J-55, 192 jts. down to packer (Halliburton R-4), 17 jts. down to 1.78" & #8221; seating nipple on bottom @ 6612' & #8217;.

3) RIH with Composite Bridge plug and RTTS packer on 2.375" & #8217; tubing string, set BP @ 6370' & #8217;., set packer and test plug is holding (top perf @ 6394' & #8217;.). Pump two sacks of sand on top of BP.

4) Pull up and isolate casing leak. If leak is small interval we may want to squeeze Flow Guard L and follow with cement squeeze, if leak is large interval or in multiple locations proceed with

14. I hereby certify that the foregoing is true and correct.

Electronic Submission #9998 verified by the BLM Well Information System  
For CONOCO INC., sent to the Farmington  
Committed to AFMSS for processing by Lucy Bee on 05/21/2002 ()

Name (Printed/Typed) DEBORAH MARBERRY

Title SUBMITTING CONTACT

Signature

(Electronic Submission)

Date 01/08/2002

## THIS SPACE FOR FEDERAL OR STATE OFFICE USE

Approved By

Title Petr. Eng.

Date 6/10/02

Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Office BLM-FFO

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

\*\* ORIGINAL \*\* ORIGINAL \*\* ORIGINAL \*\* ORIGINAL \*\* ORIGINAL \*\* ORIGINAL \*\* ORIGINAL \*\*

UNOCOD

## Additional data for EC transaction #9998 that would not fit on the form

### 32. Additional remarks, continued

slim hole procedure.

5)TIH with 3.75" OD Wooley slim hole pipe, (make up Wooley x 8rd cross over to TRW valve for well control), tag plug @ 6360', unload well with air if possible,  
Wooley FJ-60-H Hook Thread Casing Performance Data - 3.75" OD, 3.25" ID, 3.125" drift, 9.35 Lb./Ft., wall thickness 0.250", grade J-55, 90,000# tensile, min. parting load 158K lbs., maximum string set depth 8449', torque = 8 ft/LB min., & 15 ft/LB max.

6)Cement Wooley slim hole pipe in place to surface as per BJ's procedure, pump displacement plug, shut in, wait on cement.

7)TIH with work string and 3.125" bit, drill out composite plug @ 6360', clean out to 6675', blow hole dry and POOH laying down.

8)TIH with 2.375 CS Hydril, 4.7", IJ, tubing (2.70" OD connection) with SN & mule shoe on bottom, land @ 6600' plus or minus one joint.

9)Notify operator, swab if necessary and put on plunger lifted production. Watch well closely for first two weeks of production. Notify engineering of difficulties.