(SUBMIT IN TRIPLICATE)

0

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

Land Office	Santa Pe
Lease No	SF-076958
Unit I	

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	
ATOMERA	SUBSPOUENT PERCENT OF THE
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF ALTERING CASING
MUTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUBSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO ABANDON WELL	WELL HISTORY
(INDICATE ABOVE BY CHECK MADE	4 S. O. V. AN R.S. N.
	NATURE OF REPORT, NOTICE, OR OTHER DATA)
	April 17, 19.5
N See and See Vision	S line and 1850 ft. from W line of sec. 10
(Twp.)	Range) (Meridian)
Ttoo Pictured Cliffs (Field)	Jun
he elevation of the derrick floor above sea leve	Subdivision) (State or Territory)
flush, 10,000 lbs. sand. B	m 2206-16 with h shots per foot. gallons water, 9,199 gallons reakdown pressure 1200 lbs, Treating ressure 300 lbs., Injection Rate an 221h; of 1stabing landed at
flush, 10,000 lbs. sand. B pressure 1050 lbs., Final p Shell barrels per minute. Re 222h. S I G h-lh-56.	reskdown pressure 1200 lbs, Treating ressure 300 lbs., Injection Rate an 221h' of 1" tabing landed at
flush, 10,000 lbs. sand. By pressure 1050 lbs., Final public larrels per minute. R. 222h. S I G h-11-56. understand that this plan of work must receive approval in writing pany.	reskdown pressure 1200 lbs, Treating ressure 300 lbs., Injection Rate an 221h' of 1" tabing landed at
flush, 10,000 lbs. sand. B pressure 1050 lbs., Final p Shell barrels per minute. Re 222h. S I G h-lh-56.	reskdown pressure 1200 lbs, Treating ressure 300 lbs., Injection Rate an 221h' of 1" tabing landed at
flush, 10,000 lbs. sand. By pressure 1050 lbs., Final public larrels per minute. R. 222h. S I G h-11-56. understand that this plan of work must receive approval in writing pany.	reskion pressure 1200 lbs. Treating ressure 300 lbs., Direction Rate in 221h of 1st inbing landed at
pressure 1050 lbs., Final paragraph of barrels per sinute. Reserved that this plan of work must receive approval in writing pany 1272 OIL & GAS COPPARY lress P. O. Box 786	reskdown pressure 1200 lbs, Treating ressure 300 lbs., Injection Rate an 221h' of 1" tabing landed at