



(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office **Santa Fe, N. M.**

Lease No. **078197**
SE **Sec. 9-29-10**
Unit

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF	<input checked="" type="checkbox"/>
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Aztec, New Mexico February 11, 1957

Bright
2
Well No. **2** is located **1700** ft. from **N** line and **975** ft. from **E** line of sec. **9**
S 2 Sec. 9 (1/4 Sec. and Sec. No.) **29** **10** **NMPM**
Blanco (Field) **San Juan** (County or Subdivision) **New Mexico** (State or Territory)

The elevation of the derrick floor above sea level is **5719** ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Spudded 2-8-1957

On 2-9-57 we set 9 5/8" 32 lb. casing at 129 ft. Larkin Guide shoe. Pipe set on bottom of 12 1/2" hole and cemented with 75 sacks cement. Cement circulated to bottom of cellar. We tested surface pipe with 600 pressure for 30 minutes. Drilled out shoe and retested with 600 for 30 minutes. Pipe held pressure O.K. Tested 2-10-57.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company **Wood River Oil & Refining Co., Inc.**

Address **321 West Douglas**

Wichita, Kansas

By **A. J. Jackson**
Title **Representative**

