Ferm 3160-5 (Anvember 1983) (Formerly 9-331)	UNITED STATE DEPARTMENT OF THI BUREAU OF LAND MAI	E INTERIOR	SUBMIT IN TRIPLICATE* (Other instructions on reverse side)	Budget Bureau N Expires August 5. LEASE DESIGNATION NOG-8702-1:	31, 1985 IND SERIAL NO L16
(Do not use this fo	ORY NOTICES AND RE	pen or plug back	to a different reservoir.	NAVAJO	
1. OIL The GAS	7			7. UNIT AGREEMENT NA	K I
WELL X WELL 2. NAME OF OPERATOR	SHTO			8. FARM OR LEASE NAM	<u> </u>
CHUSKA ENERG	GY COMPANY	RATTLESNAKE 3-12-29N19W			
3. ADDRESS OF OPERATOR		. W 07401		9. WALL NO.	
315 N. BEHRI	END, FARMINGTON, No port location clearly and in accordance	10. PIELD AND POOL, OR WILDCAT			
See also space 17 belov At surface	1663	RATTLESNAKE DAKOTA			
746		11. SEC., T., E., M., OR BI SURVEY OR ARMA	E. AND		
.940 F	SL & 185 3′ FWL	12-T.29N-R	.19W		
14. PERMIT NO.	15. ELEVATIONS (Sh	ow whether DF, RT,	GR, etc.)	12. COUNTY OR PARISH	
	5305			SAN JUAN	N.M
16.	Check Appropriate Box To	Indicate Natur	re of Notice, Report, or C	ther Data	
NO	TICE OF INTENTION TO:	1	80888Q0	ENT REPORT OF:	
TEST WATER SHUT-OFF	PULL OR ALTER CASIN	c	WATER SHUT-OFF PRACTURE TREATMENT	REPAIRING W	
SHOOT OR ACIDIZE	ABANDON®		SHOOTING OR ACIDIZING	ABANDONMEN	r•
REPART WELL	CHANGE PLANS		(Other)	of multipie completion of	n Well
(Other) RE-ENT	COMPLETED OPERATIONS (Clearly sta-	to all partinent dat	Completion or Recompl	etion Report and Log for	n.)
This well w	well is directionally drilled, give an	vn as Ratt	clesnake 148, og		
Petroleum Com	pany under Lease b	NO. 1-89-1	- 00.		
The well wi	ll be re-entered	to flow te	est Dakota sand	by flowing i	nto a
steel test ta	nk				
and acidized. A general o	n results of test Exact completion perational porcedu	n techniqu	le will depend o	3-842 may be on test resul	squeezea ts.
CEIV (CEIV 2 AM	Y. KEW		D	ECEIVE	
Lings on the	27.	المستطوير	ש		
FEB MOTO			,	MAR 01(1989)	
50 %	THE STATE OF THE S		,	ON. DI	V.]
i£'	(-		•	DIL CON. DI	. · · · · ·
18. I hereby certify that t	he foregoing is true and correct			4 /	. , 2
SIGNED TO	Mindele	TITLE Pro	duction Mgr.	DATE J-/	7 (
(This space for Federa	al or State office use)			A 27.4	
APPROVED BY		TITLE		DATE	COVED
CONDITIONS OF API	PROVAL, IF ANY:			AS A	MENDED
				FEB	3 4 1389

*See Instructions on Reverse Side

Workover and Testing Prognosis Rattlesnake Dakota Field San Juan Co., New Mexico

Nine (9) wells in the Rattlesnake Dakota Field are to be reentered and tested by Chuska Energy Company. These wells are all at least 26 years old and a lot of the well information is either incomplete or missing. We have inspected the area and found at least six (6) of the wells are capable of flowing oil at this time. Because of the nature of the wells and the lack of information we propose to submit a general re-entry procedure and AFE. Specific procedures will be impossible to write until we determine exact well bore configurations and producing capabilities. Following is an outline of the re-entry procedure:

- Conduct archaeological clearance of well sites and access roads of those wells slated for re-entry.
- 2. Clear land damages to obtain access to wells.
- 3. Submit sundry notices and obtain water permits.
- 4. Move in test tanks and test each of the following wells that have been determined to be capable of flowing:

Rattlesnake 3-1-29N19W No. 1 (Old Well No. Unknown)	1765' FSL & 307' FWL 1- Twn.29N-Rng. 19W
Rattlesnake 3-2-29N19W No. 1 (Old Well No. Unknown)	2309' FNL & 2192' FWL 2- Twn.29N-Rng. 19W
Rattlesnake 3-2-29N19W No. 3 (Old Well No. 207)	2450' FSL & 725' FEL 2- Twn.29N-Rng. 19W
Rattlesnake 3-2-29N19W No. 4 (Old Well No. 205)	2450' FSL & 330' FEL 2- Twn.29N-Rng.19W
Rattlesnake 3-12-29N19W No. 2 (Old Well No. 148)	940' FSL & 1653' FWL 12- Twn.29N-Rng.19W
Rattlesnake 3-12-29N19W No. 5 (Old Well No. 149)	2008' FSL & 2348' FEL 12- Twn.29N-19W

Each well will be flowed at a low rate to prevent water from coning. A separate test tank will be used at each site to obtain accurate test data. Further work procedures on these wells will depend on test results.

5. The remaining three wells have fluid at or near the surface, but will not flow. The general procedure for these wells will be to run a slick line survey to determine well depth. A casing scraper and bit will be run to bottom to clean up the

casing and clear any formation debris in the hole. If the well contains 5 1/2" or grater casing, consideration will be given to running a GST (Carbon-Oxygen) log to determine the oil-water contact and passed up oil zones. Based on the log results, the well may be swabbed to test production. If it is determined that an oil-water contact exists in such manner that may cause water to be produced, a liner may be cemented in the hole. The liner would consist of either 2 3/8" or 2 7/8" tubing (depending on casing size). The Dakota would then be perforated in the oil zone and cleaned up with acid. A production test would then follow. The wells that will be tested in the above manner follow:

Rattlesnake 3-12-29N19W No.1 (Old Well No. 154)	900' FNL & 1650' FWL 12- Twn.29N-Rng.19W
Rattlesnake 3-2-29N19W No. 2 (Old Well No. 210)	2100' FSL & 500' FEL 2- Twn.29N-19W.
Rattlesnake 3-12-29N19W No.4 (Old Well No. 152)	2275' FNL & 2440' FWL 12- Twn.29N-Rng.19W
6. If the wells that are to be tes procedure similar to that in step	ted by flowing cease to flow, a 5 may be initiated in them.
APPROV	/AL_
Recommended: Production Manager July (1)	1 Date: 1/8/89
Operator Approval: V.P. Production M.C. Matter	Date: 1/18/89
President	Date:
Chairman of Board	Date:
Non-Operator Approval:	
Name:	Date:
Company:	