oso OMP ODR SEN	lute Potenti ANY ESS T T and TITLE ESSED ANY	747. J	ed Hálan								
oso MP	ANY Radea	n A Re	end								
			[				<del></del>		·	<u> </u>	<del></del>
	1585				<b></b>	+		2512	1773	<del> </del>	2.42
	Pt (psia)					(1)				F	P <sub>w</sub> P <sub>c</sub>
	$P_{\mathbf{W}}$	Pt.		1-e <sup>-s</sup>	(F <sub>c</sub> Q) <sup>2</sup>	(F	c <sup>Q</sup> ) <sup>2</sup> -e-s)	P <sub>c</sub>	P <sub>c</sub> -P <sub>w</sub> <sup>2</sup>		
ıvi	iquid Hydro ty of Liquid	l Hydr	ocarbo	ons		essure concept of the		Speci Speci	fic Gravi	ty Flow	arator Gas ving Fluid
					Din	reeima a	A COTTE A TOT	ONG			
				_					<del> </del>		
<u>+</u>	12.3650		V ''W	rI	282	1.0039	T	.9393	F <sub>pv</sub>		3396
	Coefficio	ł	$\sqrt{h_{Wl}}$		Pressure psia	FLOW CAL Flow Fac	Temp.	Gravity Factor	Compre Facto		Rate of Flow Q-MCFPD @ 15.025 psid
		3/4		270		560			1573	<b>†</b>	3 hrs
							2058	-	2041	<del> </del>	
I	Size		•	psi	g h <sub>w</sub>	°F.	<del>                                     </del>	° <sub>F</sub> .	psig	³F∙	of Flow
0.	(Prover) (Line)	(Cho	Flow Doke) Fice)	Pres	s. Diff.	Temp.	Tubing Press		Press.		3
est	ted Through								Type Tar	os	
							ED DATA		•		
ate	e of Complet	ion:	5-5-60		Packe	r	Sir	Type wo ngle-Brade Reserve	enhead-G. oir Temp.	G. or	G.O. Dual
											ess
											17
											42
ni	t <b>3</b> S										
	tial										5-17-60
om											un.

## INSTRUCTIONS

This form is to be used for reporting multi-point back pressure tests on gas wells in the State, except those on which special orders are applicable. Three copies of this form and the back pressure curve shall be filed with the Commission at Box 871, Santa Fe.

The log log paper used for plotting the back pressure curve shall be of at least three inch cycles.

## NOMENCLATURE

- Q = Actual rate of flow at end of flow period at W. H. working pressure ( $P_{\rm W}$ ). MCF/da. @ 15.025 psia and 60° F.
- $P_c$  72 hour wellhead shut-in casing (or tubing) pressure whichever is greater. psia
- Pw Static wellhead working pressure as determined at the end of flow period. (Casing if flowing thru tubing, tubing if flowing thru casing.) psia
- $P_t$  Flowing wellhead pressure (tubing if flowing through tubing, casing if flowing through casing.) psia
- $P_{f}$  Meter pressure, psia.
- hw Differential meter pressure, inches water.
- Fg Gravity correction factor.
- Ft Flowing temperature correction factor.
- Fpv Supercompressability factor.
- n I Slope of back pressure curve.
- Note: If  $P_{w}$  cannot be taken because of manner of completion or condition of well, then  $P_{w}$  must be calculated by adding the pressure drop due to friction within the flow string to  $P_{t}$ .

STATE OF HEW MEXICO								
OIL COIL TVATION COMMISSIO								
AL TO DISTRICT OFFICE								
MSUNDER UT OFF AL	CEVILOER		3					
	J 1	t!						
[TSILL 1]		1						
[								
	1 011							
7R5. CLT 3	6.3		<del> </del>					
From Head Of 2E								
. UCE WATER								