Faria 9-331 (May 1963)	DEDART	UNITED STATES MENT OF THE INTERIO	SUBMIT IN TRIPLICATE®	Form approve Budget Bures 5. LEASE DESIGNATION	u No. 42-R1424.
		SEOLOGICAL SURVEY	91 () true 2 -2-7,	1-89-IND-	56
			N. 1. 1. C	6. IF INDIAN, ALLOTTEE	
	SUNDRY NOT	ICES AND REPORTS C	ON WELLS		
(Do not u	Use "APPLICA	Navajo			
1.				7. UNIT AGREEMENT NA	ME
WELL A	YELL OTHER			8. FARM OR LEASE NAM	<u> </u>
2. NAME OF OPER	ATOR	Continental Oil Comp	227	Rattlesnal	
S. ADDRESS OF OF	ERATOR	Continental off comp	· = D	9. WELL NO.	C GOV L
6. 2 002202		152 North Durbin, Caspar, Wyo. 82601			2
4. LOCATION OF W	ELL (Report location c	clearly and in accordance with any it to requirements.		10. FIELD AND POOL, OR	
See also space 17 below.) At surface		1980' FNL, 1980' FWL (Unit Langer F)		Rattlesnake	
				11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA	
		OIL	CONSENTATE	San 12 '	תוס בים מאס מים
14. PERMIT NO.		15. ELEVATIONS (Show whether DF,		Sec. 12,	13. STATE
14. FERMIT NO.		53!	89' DF	San Juan	New Mexico
					-
16.	•	opropriate Box To Indicate N		PENT REPORT OF:	
	NOTICE OF INTER	TION TO:	2083Edr	¬	
TEST WATER	SHUT-OFF	PULL OB ALTER CASING	WATER SHUT-OFF	REPAIRING W	
FRACTURE TRI	·	MULTIPLE COMPLETE	FRACTURE TREATMENT	ALTERING CA	
SHOOT OR ACI		ABANDON* CHANGE PLANS	SHOOTING OR ACIDIZING (Other)		
REPAIR WELL (Other)	لــا	CHANGE FEARS	(Nort: Report results	of multiple completion eletion Report and Log for	on Well m.)
	ork. If well is directly	ERATIONS (Clearly state all pertinent conally drilled, give subsurface locat	t details, and give pertinent dates, ions and measured and true vertice	including estimated dated dated dated all depths for all markers	e of starting any and zones perti-
•• 11 ***	TD 6816	5'. 13 3/8" surface	casino, 48", H-40 set	at 320' and 9	5/8"
Intermed:	ista casino 3	86#T-55 set at 4650	'. Production casing	z, /", 23#, J-3	5 set
at 66881	Open-hole	6688-6816'. Well Sta	tus: Oil temporarily	shut-in.	
					FOUND
We propos	se to plug the	e well as follows:		R	IP[IAFD
	Spot -20-00	rok-coment-plug-64 20-	65201.		·.
	Spot 25	-lug-in-ourface-casin	gt	UU	ST 27 1971
	Set 10' 16	ength of 4" pipe in s	urface plug so that I	It brolecus ar	CON. COM.
	least 4'	above the ground lewill be capped and a	ver. marker attached or v	welded on pipe.	DIST 3
	-				01011
	200° (cement plug 6400-6600 5575-5700 "	,• •	The state of the s	
	100*	* * 4300- 1 400			interest and
		surface plug with max			
				AUG 2 4 1	9/1
•			R . ; 'e'		
			1	U.S. GEOLOGICAL FAMMENCTON,	SURVEY
	NN(00000(0) T	(1.0 (2)	· L	Fig. 1. 2014 Co. F. William	
USGS (6)	NMOGCC (2) F:				
18. 1 hereby certi			inistrative Supervise	or DATE 8-	18-71
SIGNED	emer L. U	TITLE Adm	THISTISTIVE SUPERVIEW	DATE	
(This space f	or Federal or State of	ice use)			
APPROVED 1	R ∀	TITLE		DATE	
CONDITIONS	OF APPROVAL, IF			•	

SUBMIT IN TRIPLICATE.