

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office Sanita Fe
Lease No. 067777-4
Unit _____

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	<input checked="" type="checkbox"/>	SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF		SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL		SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE		SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING		SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL			

RECEIVED
DEC 28 1960

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

U. S. GEOLOGICAL SURVEY
SARASOTA, NEW MEXICO

Well No. 1 is located 1180 ft. from (N) line and 790 ft. from (W) line of sec. 10
R4/4 Section 10 R2N 12W 124N
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Undesignated San Juan New Mexico
(Field) (County or Subdivision) (State or Territory)

The elevation of the ground level floor above sea level is 5679 ft.


DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

We propose to drill a well at the above location using rotary tools from surface to TD as follows:

1. Drill 12 1/4" hole to 250'.
2. Run & cement 250' 8 1/8" OD, 2 1/2" ID. Circ. cut. to surface.
3. WOC 2 1/2" ID. Pressure test log.
4. Drill 7 7/8" hole to TD (approx. 6500').

(over)



I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Tennessee Gas Transmission Company

Address P. O. Box 1714

Durango, Colorado

By L. B. Fink

Title District Production Superintendent

5. Run & test. 6500' (approx) & 1/2" OD, 9.5# csg. Test in 2 stages as follows:

(1) 250 sc

(2) Stage collar 50' below base of Pictured Cliffs.
Test w/ 50 sc or sufficient volume to test 50'
above P. C.

6. Potential well & clean up loc.

7. All work to conform to USGS & BACC regulations.