

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

1-89-IND-56

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Rattlesnake Gov't.

9. WELL NO.

146

10. FIELD AND POOL, OR WILDCAT

Rattlesnake - Penn. BCD

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 11, T29N, R19W

12. COUNTY OR PARISH 13. STATE

San Juan

New Mexico

1.

OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

Continental Oil Company

3. ADDRESS OF OPERATOR

152 North Durbin, Casper, Wyo. 82601

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)

At surface

660' FNL, 1980' FNL (Unit Letter C)

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

5262' RB

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT*

(Other)

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Well History: TD 6695', Surface casing, 13 3/8", 48#, H-40 set at 310' and intermediate casing, 9 5/8", 36#, J-55 set at 4520'. Production casing, 7", 23#, J-55 set at 6561'. Open-hole 6561-6695'. Well Status: Gas flowing.

We propose to plug the well as follows:

Spot 100' cement plug from 6250-6350' in 7" liner.
Spot 25' plug in surface casing.
Set 10' length of 4" pipe in surface plug so that it projects at least 4' above ground level.
Top of 4' will be capped and a marker attached or welded on pipe.

USGS(6) NMOGCC(2) File(2)

18. I hereby certify that the foregoing is true and correct

SIGNED

Elmer L. Phillips

TITLE

Administrative Supervisor

DATE

8-18-71

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

SA

*See Instructions on Reverse Side



AUG 24 1971