



(SUBMIT IN TRIPLICATE)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

Land Office \_\_\_\_\_  
Lease No. 28469  
Unit Murphy

## SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL _____	<input checked="" type="checkbox"/>	SUBSEQUENT REPORT OF WATER SHUT-OFF _____
NOTICE OF INTENTION TO CHANGE PLANS _____		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING _____
NOTICE OF INTENTION TO TEST WATER SHUT-OFF _____		SUBSEQUENT REPORT OF ALTERING CASING _____
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL _____		SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR _____
NOTICE OF INTENTION TO SHOOT OR ACIDIZE _____		SUBSEQUENT REPORT OF ABANDONMENT _____
NOTICE OF INTENTION TO PULL OR ALTER CASING _____		SUPPLEMENTARY WELL HISTORY _____
NOTICE OF INTENTION TO ABANDON WELL _____		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

April 15, 1953

Well No. 1-2 is located 1650 ft. from N line and 990 ft. from E line of sec. 1

Section 2 (1/4 Sec. and Sec. No.) 24 (Twp.) 11 (Range) T. 24 N. R. 11 E. (Meridian)  
Sec. 24 (Field) San Juan (County or Subdivision) Col. 4 (State or Territory)

The elevation of the derrick floor above sea level is 5672 ft.

### DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

It is intended to drill well and rotary tools to the base of the Cliff formation, which is the well with well tools to determine the thickness of the Cliff formation approximately 2000 ft. per foot. Total depth 1061.

Log: \_\_\_\_\_

9 5/8" surface casing set at 140' with a cement plug at surface.  
5 1/2" production casing set at 140' with a cement plug at surface.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company \_\_\_\_\_

Address \_\_\_\_\_

By [Signature]

Title Controller Engineer.

