		3 117 1/2 3 2 12				/
		1-HLKendrick				7
NO. OF COP	IES RECEIVED 3	1-JTHampton				Form C-103 Supersedes Old
DISTRI	BUTION	1-F		n		C-102 and C-103
SANTA FE		NEW MEXICO	OIL CONSI	ERVATION COM	MISSION	Effective 1-1-65
FILE	119			1981	10	Control Tomo of Loggo
U.S.G.S.					1158	5a. Indicate Type of Lease State Fee. X
LAND OFF	ICE				A PTI /	
OPERATOR	R /			$\sqrt{ I_{E}(r_{2}) }$	1	5. State Oil & Gas Lease No.
					= 1970	
	SUNDR	Y NOTICES AND REF	PORTS ON	MELIESE B	,, (0.	
(00 1	NOT USE THIS FORM FOR PRO- USE "APPLICATI	POSALS TO DRILL OR TO DEE ON FOR PERMIT —** (FORM C	PEN OR PLUG B	H PROPOSALS.)	COM	
I.	GAS X	OTHER-		OIL COL	7.3	7. Unit Agreement Name
2. Name of O	perator			-		8. Farm or Lease Name
BETA	DEVELOPMENT CO.	A (1)				Martin "A"
3. Address of			_			9. Well No.
125 P	etroleum Club Pl	aza, Farmington	N.M.			1
4. Location o	of Well	 ,				10. Field and Pool, or Wildcat
		.775	South	LINE AND	1575	Basin Dakota
UNIT LET	TTER	FEET FROM THE		LINE AND	FEET FROM	
E	ast	3 TOWNS	29 N		11 W NMPM	
тне	LINE, SECTION	ON TOWNS	HIP	RANGE	RMPM	
mm	mmmm	15. Elevation (Show whether	DF, RT, GR, etc.)	12. County
///////				.6 GR		San Juan
16.	mininininininininininininininininininin	11111Y			as Report or O	ther Data
		Appropriate Box To	indicate N	vature of Noti	ce, Report of O	T REPORT OF:
	NOTICE OF IN	ITENTION TO:			SUBSEQUEN	TREFORT OF
					T.	ALTERING CASING
PERFORM REI	MEDIAL WORK	PLUG AND	ABANDON	REMEDIAL WORK	X	PLUG AND ABANDONMENT ,
TEMPORARIL	Y ABANDON			COMMENCE DRIL	<u> </u>	PEUG AND ABARDONMENT
PULL OR ALT	ER CASING	CHANGE PL	ANS	CASING TEST AN	CEMENT JOB	
			·	OTHER		 L_
OTHER						
	To Completed O	andtona (Clearly state al.	l nertinent det	tails, and give per	tinent dates, includin	g estimated date of starting any proposed
17. Describe	EE RULE 1 103.	perditions (Cicarty State and	p 0.00.00.00	,		
	The second seconds on	ver unit. remove	d well he	ead, rigged	in BaOaPa I	
	8 rd J-55 tbg) 6 6330°. Loaded Picked up RTTS packer up & down Picked packer up Followed w/200 9 Pumped in 1/2 bl back 1/4 bbl	out of hole. Pid hole & circ. of hole & circ. of hole to find hole to 3286, sx reg Neet w/tbol., pressured ureleased packer.	n top of g, set pa ole in ca set pack g & tool p to 1300 POH.	cast iron h bridge plu acker @ 460 sg - found ker & squee clear w/wa 0#, SI 1/2	ridge plug & g l hr. Tes: 00'. Tested of top hole @ 30 ezed w/200 sx ater. Pressurhr. Holding	Pulled 206 jts (2-3/8" ran in hole on tbg. set ted to 1500#, held OK. POH. csg below to 1200#. Picked 596', bottom hole @ 4020'. reg + 2% calcium chloride. red up to 1000#, SI 1/2 hr. 1000# after 1/2 hr, bled
L/ 27/7 0	8 rd J-55 tbg) 6 6330°. Loaded Picked up RTTS packer up & down Picked packer up Followed w/200 9 Pumped in 1/2 bl back 1/4 bbl., 5 Finished trip of cement @ 3410°, held OK. Drille tested all csg 13 min., pushed	out of hole. Pid hole & circ. of hole & circ. of hole to find hole to 3286, sx reg Neet w/tbol., pressured ureleased packer, ut of hole, laye circ., WOC 12 hed 100° cement & to 1200#, held 0 plug down hole	n top of g, set pa ole in conset pack g & tool p to 1300 POH. d down R' rs. Pre- tested of K. Tagg 5° below	cast iron he bridge plus acker @ 460 sg - found ker & squee clear w/wa 0#, SI 1/2 TTS packer, ssure teste csg. Drill ed cast iron all csg pe	ridge plug & g l hr. Tested of top hole @ 30 ezed w/200 sx ter. Pressur hr. Holding picked up 3 ed 4-1/2" csg ted solid cemon bridge pluerforations.	ran in hole on tog. set ted to 1500#, held OK. POH. csg below to 1200#. Picked 596', bottom hole @ 4020'. reg + 2% calcium chloride. red up to 1000#, SI 1/2 hr. 1000# after 1/2 hr, bled -7/8" bit. WIH, tagged above cement to 1200#, ent to 4025'. Pressure g @ 6330', drilled out in POH.
/ 27/7 0	8 rd J-55 tbg) 6 6330°. Loaded Picked up RTTS packer up & down Picked packer up Followed w/200 s Pumped in 1/2 bl back 1/4 bbl., Finished trip of cement @ 3410°, held OK. Drille tested all csg 13 min., pushed Finished trip of packet packet.	but of hole. Pid hole & circ. of hole & circ. of hole to find hole to 3286, sx reg Neet w/tbol., pressured ureleased packer, ut of hole, laye circ., WOC 12 hed 100' cement & to 1200#, held of plug down hole ut w/bit. Start	n top of g, set pace ole in conset pace g & tool p to 1300 POH. d down R' rs. Pre- tested K. Tagg 5' below ed in ho	cast iron he bridge plus acker @ 460 sg - found ker & squee clear w/wa 0#, SI 1/2 TTS packer, ssure teste csg. Drilled cast iron all csg pele w/produc	ridge plug & g l hr. Tested of top hole @ 30 zed w/200 sx ter. Pressur hr. Holding picked up 30 ded 4-1/2" csg led solid cemon bridge plue rforations.	ran in hole on tog. set ted to 1500#, held OK. POH. csg below to 1200#. Picked 596*, bottom hole @ 4020*. reg + 2% calcium chloride. red up to 1000#, SI 1/2 hr. 1000# after 1/2 hr, bled -7/8" bit. WIH, tagged above cement to 1200#, ent to 4025*. Pressure g @ 6330*, drilled out in POH. w/bar collar 1 jt off bottom
/ 27/7 0	8 rd J-55 tbg) 6 6330°. Loaded Picked up RTTS packer up & down Picked packer up Followed w/200 Pumped in 1/2 bl back 1/4 bbl., Finished trip of cement @ 3410°, held OK. Drille tested all csg 13 min., pushed Finished trip of tbg hung in str	but of hole. Pid hole & circ. of hole & circ. of hole to find he hole to 3286', ax reg Neet w/tb bl., pressured ureleased packer, but of hole, layer circ., WOC 12 hed 100' cement & to 1200#, held of plug down hole but w/bit. Start ipper rubber fel	n top of g, set pa ole in conset pack g & tool p to 1300 POH. d down R' rs. Pre- tested K. Tagg 5' below ed in ho 1 free,	cast iron he bridge plus acker @ 460 sg - found ker & squee clear w/wa 0#, SI 1/2 TTS packer, ssure teste csg. Drilled cast iron all csg per le w/producelevators	ridge plug & g l hr. Tested of top hole @ 30 zed w/200 sx ter. Pressur hr. Holding picked up 30 ded 4-1/2" csg led solid cemon bridge plue rforations.	ran in hole on tog. set ted to 1500#, held OK. POH. csg below to 1200#. Picked 596*, bottom hole @ 4020*. reg + 2% calcium chloride. red up to 1000#, SI 1/2 hr. 1000# after 1/2 hr, bled -7/8" bit. WIH, tagged above cement to 1200#, ent to 4025*. Pressure g @ 6330*, drilled out in POH. w/bar collar 1 jt off bottom
/27/70 /28/70	8 rd J-55 tbg) 6 6330°. Loaded Picked up RTTS packer up & down Picked packer up Followed w/200 Pumped in 1/2 bl back 1/4 bbl., Finished trip of cement @ 3410°, held OK. Drille tested all csg 13 min., pushed Finished trip of tbg hung in stranger. Fisher	but of hole. Pid hole & circ. of hole & circ. of hole to find he hole to 3286, sx reg Neet w/tb bl., pressured wreleased packer, ut of hole, layer circ., WOC 12 hed 100° cement & to 1200#, held of plug down hole ut w/bit. Start ipper rubber feld out the w/tbg	n top of g, set pace ole in conset pace g & tool p to 1300 POH. d down R' rs. Pre tested K. Tagg 5' below ed in ho 1 free,	cast iron he bridge plus acker @ 460 sg - found ker & squee clear w/wa 0#, SI 1/2 TTS packer, ssure teste csg. Drilled cast iron all csg per le w/produce elevators is trips).	ridge plug & g l hr. Tested top hole @ 35 ezed w/200 sx ter. Pressur hr. Holding picked up 3 ed 4-1/2" csg led solid cemen bridge plus rforations. etion string parred open & g larged open &	ran in hole on tog. set ted to 1500#, held OK. POH, csg below to 1200#. Picked 596', bottom hole @ 4020'. reg + 2% calcium chloride. red up to 1000#, SI 1/2 hr. 1000# after 1/2 hr, bled -7/8" bit. WIH, tagged above cement to 1200#, ent to 4025'. Pressure g @ 6330', drilled out in POH. w/bar collar 1 jt off bottom dropped 8 jts tbg from
/27/70 /28/70	8 rd J-55 tbg) 6 6330°. Loaded Picked up RTTS packer up & down Picked packer up Followed w/200 s Pumped in 1/2 bl back 1/4 bbl., Finished trip or cement @ 3410°, held OK. Drille tested all csg 13 min., pushed Finished trip or tbg hung in strip or tbg hung in strip surface. Fisher 2-2/8" tbg	but of hole. Pid hole & circ. of hole & circ. of hole to find he hole to 3286, sx reg Neet w/tb bl., pressured ureleased packer, ut of hole, layer circ., WOC 12 hed 100° cement & to 1200#, held of plug down hole ut w/bit. Start ipper rubber feld out tbg w/tbg in hole w/har co	n top of g, set pace ole in conset pace g & tool p to 1300 POH. d down R' rs. Pre tested K. Tagg 5' below ed in ho 1 free, spear (3	cast iron he bridge plus acker @ 460 sg - found ker & squee clear w/wa 0#, SI 1/2 TTS packer, ssure teste csg. Drilled cast iron all csg per le w/produce elevators is trips).	ridge plug & g l hr. Tested top hole @ 35 ezed w/200 sx ter. Pressur hr. Holding picked up 3 ed 4-1/2" csg led solid cemon bridge plus erforations. Etion string farred open & m. ran 206 i	ran in hole on tog. set ted to 1500#, held OK. POH, csg below to 1200#. Picked 596', bottom hole @ 4020'. reg + 2% calcium chloride. red up to 1000#, SI 1/2 hr. 1000# after 1/2 hr, bled -7/8" bit. WIH, tagged above cement to 1200#, ent to 4025'. Pressure g @ 6330', drilled out in POH. w/bar collar 1 jt off bottom dropped 8 jts tbg from ts 2-3/8" EUE J-55 tbg(6506
/27/70 ./28/70	8 rd J-55 tbg) 6 6330°. Loaded Picked up RTTS packer up & down Picked packer up Followed w/200 s Pumped in 1/2 bl back 1/4 bbl., Finished trip or cement @ 3410°, held OK. Drille tested all csg 13 min., pushed Finished trip or tbg hung in strip or tbg hung in strip surface. Fisher 2-2/8" tbg	but of hole. Pid hole & circ. of hole & circ. of hole to find he hole to 3286, sx reg Neet w/tb bl., pressured ureleased packer, ut of hole, layer circ., WOC 12 hed 100° cement & to 1200#, held of plug down hole ut w/bit. Start ipper rubber feld out tbg w/tbg in hole w/har co	n top of g, set pace ole in conset pace g & tool p to 1300 POH. d down R' rs. Pre tested K. Tagg 5' below ed in ho 1 free, spear (3	cast iron he bridge plus acker @ 460 sg - found ker & squee clear w/wa 0#, SI 1/2 TTS packer, ssure teste csg. Drilled cast iron all csg per le w/produce elevators is trips).	ridge plug & g l hr. Tested top hole @ 35 ezed w/200 sx ter. Pressur hr. Holding picked up 3 ed 4-1/2" csg led solid cemon bridge plus erforations. Etion string farred open & m. ran 206 i	ran in hole on tog. set ted to 1500#, held OK. POH. csg below to 1200#. Picked 596', bottom hole @ 4020'. reg + 2% calcium chloride. red up to 1000#, SI 1/2 hr. 1000# after 1/2 hr, bled -7/8" bit. WIH, tagged above cement to 1200#, ent to 4025'. Pressure g @ 6330', drilled out in POH. w/bar collar 1 jt off bottom dropped 8 jts tbg from ts 2-3/8" EUE J-55 tbg(6506
/27/70 ./28/70	8 rd J-55 tbg) 6 6330°. Loaded Picked up RTTS packer up & down Picked packer up Followed w/200 s Pumped in 1/2 bl back 1/4 bbl., Finished trip or cement @ 3410°, held OK. Drille tested all csg 13 min., pushed Finished trip or tbg hung in strip or tbg hung in strip surface. Fisher 2-2/8" tbg	but of hole. Pid hole & circ. of hole & circ. of hole to find he hole to 3286, sx reg Neet w/tb bl., pressured ureleased packer, ut of hole, layer circ., WOC 12 hed 100° cement & to 1200#, held of plug down hole ut w/bit. Start ipper rubber feld out tbg w/tbg in hole w/har co	n top of g, set pace ole in conset pace g & tool p to 1300 POH. d down R' rs. Pre tested K. Tagg 5' below ed in ho 1 free, spear (3	cast iron he bridge plus acker @ 460 sg - found ker & squee clear w/wa 0#, SI 1/2 TTS packer, ssure teste csg. Drilled cast iron all csg per le w/produce elevators is trips).	ridge plug & g l hr. Tested top hole @ 35 ezed w/200 sx ter. Pressur hr. Holding picked up 3 ed 4-1/2" csg led solid cemon bridge plus erforations. Etion string farred open & m. ran 206 i	ran in hole on tog. set ted to 1500#, held OK. POH, csg below to 1200#. Picked 596', bottom hole @ 4020'. reg + 2% calcium chloride. red up to 1000#, SI 1/2 hr. 1000# after 1/2 hr, bled -7/8" bit. WIH, tagged above cement to 1200#, ent to 4025'. Pressure g @ 6330', drilled out in POH. w/bar collar 1 jt off bottom dropped 8 jts tbg from ts 2-3/8" EUE J-55 tbg(6506
./27/70 ./28/70	8 rd J-55 tbg) 6 6330°. Loaded Picked up RTTS packer up & down Picked packer up Followed w/200 spumped in 1/2 bl back 1/4 bbl., spinished trip of cement @ 3410°, held OK. Drille tested all csg 13 min., pushed Finished trip of tbg hung in strisurface. Fisher Ran 2-3/8" tbg landed @ 6516°.	but of hole. Pid hole & circ. of hole & circ. of hole to find hole to find hole to 3286, sx reg Neet w/tbol., pressured ureleased packer, ut of hole, layed circ., WOC 12 hed 100° cement & to 1200#, held of plug down hole ut w/bit. Start ipper rubber feld out tbg w/tbg in hole w/bar cores nabove is true and completed by:	n top of g, set pace ole in conset pace g & tool p to 1300 POH. d down R' rs. Pre tested K. Tagg 5' below ed in ho 1 free, spear (3	cast iron he bridge plus acker @ 460 sg - found ker & squee clear w/wa 0#, SI 1/2 TTS packer, ssure teste csg. Drilled cast iron all csg per le w/produce elevators is trips).	ridge plug & g l hr. Tested top hole @ 35 ezed w/200 sx ter. Pressur hr. Holding picked up 3 ed 4-1/2" csg led solid cemon bridge plus erforations. Etion string farred open & m. ran 206 i	ran in hole on tog. set ted to 1500#, held OK. POH, csg below to 1200#. Picked 596', bottom hole @ 4020'. reg + 2% calcium chloride. red up to 1000#, SI 1/2 hr. 1000# after 1/2 hr, bled -7/8" bit. WIH, tagged above cement to 1200#, ent to 4025'. Pressure g @ 6330', drilled out in POH. w/bar collar 1 jt off bottom dropped 8 jts tbg from
./27/70 ./28/70	8 rd J-55 tbg) 6 6330°. Loaded Picked up RTTS packer up & down Picked packer up Followed w/200 s Pumped in 1/2 bl back 1/4 bbl., Finished trip or cement @ 3410°, held OK. Drille tested all csg 13 min., pushed Finished trip or tbg hung in strip or tbg hung in strip surface. Fisher 2-2/8" tbg	but of hole. Pid hole & circ. of hole & circ. of hole to find hole to find hole to 3286, sx reg Neet w/tbol., pressured ureleased packer, ut of hole, layed circ., WOC 12 hed 100° cement & to 1200#, held of plug down hole ut w/bit. Start ipper rubber feld out tbg w/tbg in hole w/bar cores nabove is true and completed by:	n top of g, set pace ole in conset pace g & tool p to 1300 POH. d down R' rs. Pre tested K. Tagg 5' below ed in ho 1 free, spear (3	cast iron he bridge plus acker @ 460 sg - found ker & squee clear w/wa 0#, SI 1/2 TTS packer, ssure tested csg. Drilled cast iron all csg pele w/producelevators is trips). t off botto head. Relation my knowledge	ridge plug & g l hr. Tested of top hole @ 30 zed w/200 sx ter. Pressur hr. Holding picked up 30 ded 4-1/2" csg ted solid cement of the plug erforations. Extra string of the plug erforations of the plug erfora	ran in hole on tog. set ted to 1500#, held OK. POH. csg below to 1200#. Picked 596*, bottom hole @ 4020*. reg + 2% calcium chloride. red up to 1000#, SI 1/2 hr. 1000# after 1/2 hr, bled -7/8" bit. WIH, tagged above cement to 1200#, ent to 4025*. Pressure g @ 6330*, drilled out in POH. w/bar collar 1 jt off bottom dropped 8 jts tbg from ts 2-3/8" EUE J-55 tbg(6506 00 AM 1-29-70/ (over)
./27/70 ./28/70	8 rd J-55 tbg) 6 6330°. Loaded Picked up RTTS packer up & down Picked packer up Followed w/200 spumped in 1/2 bl back 1/4 bbl., spinished trip of cement @ 3410°, held OK. Drille tested all csg 13 min., pushed Finished trip of tbg hung in strisurface. Fisher Ran 2-3/8" tbg landed @ 6516°.	but of hole. Pid hole & circ. of hole & circ. of hole to find hole to find hole to 3286, sx reg Neet w/tbol., pressured ureleased packer, ut of hole, layed circ., WOC 12 hed 100° cement & to 1200#, held of plug down hole ut w/bit. Start ipper rubber feld out tbg w/tbg in hole w/bar cores nabove is true and completed by:	n top of g, set pace ole in conset pace g & tool p to 1300 POH. d down R' rs. Pre tested K. Tagg 5' below ed in ho 1 free, spear (3	cast iron he bridge plus acker @ 460 sg - found ker & squee clear w/wa 0#, SI 1/2 TTS packer, ssure teste csg. Drilled cast iron all csg per le w/produce elevators is trips).	ridge plug & g l hr. Tested of top hole @ 30 zed w/200 sx ter. Pressur hr. Holding picked up 30 ded 4-1/2" csg ted solid cement of the plug erforations. Extra string of the plug erforations of the plug erfora	ran in hole on tog. set ted to 1500#, held OK. POH, csg below to 1200#. Picked 596', bottom hole @ 4020'. reg + 2% calcium chloride. red up to 1000#, SI 1/2 hr. 1000# after 1/2 hr, bled -7/8" bit. WIH, tagged above cement to 1200#, ent to 4025'. Pressure g @ 6330', drilled out in POH. w/bar collar 1 jt off bottom dropped 8 jts tbg from ts 2-3/8" EUE J-55 tbg(6506
/27/70 /28/70 /29/70	8 rd J-55 tbg) 6 6330°. Loaded Picked up RTTS packer up & down Picked packer up Followed w/200 spumped in 1/2 bl back 1/4 bbl., spinished trip of cement @ 3410°, held OK. Drille tested all csg 13 min., pushed Finished trip of tbg hung in strisurface. Fisher Ran 2-3/8" tbg landed @ 6516°.	but of hole. Pid hole & circ. of hole & circ. of hole to find hole to find hole to 3286, sx reg Neet w/tbol., pressured ureleased packer, ut of hole, layed circ., WOC 12 hed 100° cement & to 1200#, held of plug down hole ut w/bit. Start ipper rubber feld out tbg w/tbg in hole w/bar cores nabove is true and completed by:	n top of g, set pace ole in conset pace g & tool p to 1300 POH. d down R' rs. Pre tested K. Tagg 5' below ed in ho 1 free, spear (3	cast iron he bridge plus acker @ 460 sg - found ker & squee clear w/wa 0#, SI 1/2 TTS packer, ssure tested csg. Drilled cast iron all csg pele w/producelevators is trips). t off botto head. Relation my knowledge	ridge plug & g l hr. Tested of top hole @ 30 zed w/200 sx ter. Pressur hr. Holding picked up 30 ded 4-1/2" csg ted solid cement of the plug erforations. Extra string of the plug erforations of the plug erfora	ran in hole on tog. set ted to 1500#, held OK. POH. csg below to 1200#. Picked 596', bottom hole @ 4020'. reg + 2% calcium chloride. red up to 1000#, SI 1/2 hr. 1000# after 1/2 hr, bled -7/8" bit. WIH, tagged above cement to 1200#, ent to 4025'. Pressure g @ 6330', drilled out in POH. w/bar collar 1 jt off bottom dropped 8 jts tbg from ts 2-3/8" EUE J-55 tbg(6506 00 AM 1-29-70/ (over)
/27/70 /28/70 /29/70	8 rd J-55 tbg) 6 6330°. Loaded Picked up RTTS packer up & down Picked packer up Followed w/200 spumped in 1/2 bl back 1/4 bbl., spinished trip of cement @ 3410°, held OK. Drille tested all csg 13 min., pushed Finished trip of tbg hung in strisurface. Fisher Ran 2-3/8" tbg landed @ 6516°.	but of hole. Pid hole & circ. of hole & circ. of hole to find hole to find hole to 3286, sx reg Neet w/tbol., pressured ureleased packer, ut of hole, layed circ., WOC 12 hed 100° cement & to 1200#, held of plug down hole ut w/bit. Start ipper rubber feld out tbg w/tbg in hole w/bar cores nabove is true and completed by:	n top of g, set pa ole in c set pacl g & tool p to 1300 POH. d down R rs. Pre tested K. Tagg 5' below ed in ho l free, spear (3 llar l j et well te to the best	cast iron he bridge plus acker @ 460 sg - found ker & squee clear w/wa 0#, SI 1/2 TTS packer, ssure tested cast iron all csg period cast iron cast iron csg period cast iron csg period cast iron csg period csg period cast iron csg period csg csg period c	ridge plug & g l hr. Tested of top hole @ 30 zed w/200 sx ter. Pressur hr. Holding picked up 30 de 4-1/2" csg ted solid cemon bridge plus erforations. Etion string parred open & com, ran 206 j and belief.	ran in hole on tog. set ted to 1500#, held OK. POH csg below to 1200#. Picked 596', bottom hole @ 4020'. reg + 2% calcium chloride. red up to 1000#, SI 1/2 hr. 1000# after 1/2 hr, bled -7/8" bit. WIH, tagged above cement to 1200#, ent to 4025'. Pressure g @ 6330', drilled out in POH. w/bar collar 1 jt off bottom dropped 8 jts tbg from ts 2-3/8" EUE J-55 tbg(6506 00 AM 1-29-70/ (over) DATFebruary 3, 1970
/27/70 /28/70 /29/70	8 rd J-55 tbg) 6 6330°. Loaded Picked up RTTS packer up & down Picked packer up Followed w/200 spumped in 1/2 bl back 1/4 bbl., spinished trip of cement @ 3410°, held OK. Drille tested all csg 13 min., pushed Finished trip of tbg hung in strisurface. Fisher Ran 2-3/8" tbg landed @ 6516°.	but of hole. Pid hole & circ. of hole & circ. of hole to find hole to find hole to 3286, sx reg Neet w/tbol., pressured ureleased packer, ut of hole, layed circ., WOC 12 hed 100° cement & to 1200#, held of plug down hole ut w/bit. Start ipper rubber feld out tbg w/tbg in hole w/bar cores nabove is true and completed by:	n top of g, set pa ole in c set pacl g & tool p to 1300 POH. d down R rs. Pre tested K. Tagg 5' below ed in ho l free, spear (3 llar l j et well te to the best	cast iron he bridge plus acker @ 460 sg - found ker & squee clear w/wa 0#, SI 1/2 TTS packer, ssure tested csg. Drilled cast iron all csg pele w/producelevators is trips). t off botto head. Relation my knowledge	ridge plug & g l hr. Tested of top hole @ 30 zed w/200 sx ter. Pressur hr. Holding picked up 30 de 4-1/2" csg ted solid cemon bridge plus erforations. Etion string parred open & com, ran 206 j and belief.	ran in hole on tog. set ted to 1500#, held OK. POH, csg below to 1200#. Picked 596', bottom hole @ 4020'. reg + 2% calcium chloride. red up to 1000#, SI 1/2 hr. 1000# after 1/2 hr, bled -7/8" bit. WIH, tagged above cement to 1200#, ent to 4025'. Pressure g @ 6330', drilled out in POH. w/bar collar 1 jt off bottom dropped 8 jts tbg from ts 2-3/8" EUE J-55 tbg(6506 00 AM 1-29-70/ (over)

1/30/70 Rigged up swab unit, swabbed 4 hrs. Well kicked off - too wet to measure.

TO BE STORY

.