

(SUBMIT IN TRIPLICATE)

Indian Agency _____

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Navajo

Allottee _____

Lease No. 1-69-IND-96

Section 2


SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING
NOTICE OF INTENTION TO REDRILL OR REPAIR WELL	SUBSEQUENT REPORT OF REDRILLING OR REPAIR
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY X
NOTICE OF INTENTION TO ABANDON WELL	

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

November 13, 1961

Well No. 136 is located 1960 ft. from [S] line and 1980 ft. from [E] line of sec. 2
SW/4, Sec. 2 29N 19W NMPN
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Rattlesnake San Juan New Mexico
(Field) (County or Subdivision) (State or Territory)



The elevation of the derrick floor above sea level is 5257 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Spudded 9-24-60. Drld with rotary tools to T.D. 6454', PSD 6774'. Set and cemented casing as follows: 20" OD surface @ 112' with 135 sks. regular. 7" OD production string @ 6853' with stage collar at 970'. Cemented out shoe with 75 sks. regular mixed with 75 cu. ft. stratocrete followed with 75 sks. regular. Cemented out stage collar to protect Dakota formation with 75 sks. regular mixed with 75 cu. ft. stratocrete, followed with 20 sks. regular. Completed as a pumping well in Paradox as follows: Perforated with 4 jets per foot 6726'-6750', acidized with 1000 gals. 15% mud acid. Put well to pumping. IPP 39 BOPD & 390 BWPD, gravity 40.2° API, GOR 1500. On 3-28-61, perforated 6432'-6437'. Test 331 MFCGPB. Perforations shut-off. 6-1-61, perforated 6681'-6691' and installed submersible type pump. Pumped 186 BOPD & 822 BWPD.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Continental Oil Company

Address Box 1312

Durango, Colorado

Original Signed By:
H. D. HALEY

By _____

Title District Superintendent

USGS(3) NMCC(2) Bu/Mines GHO(2) HCN