NEW MEXICO OIL CONSERVATION COMMISSION

Form C-122

			M	ULTI-	POINT E	BACK PRE	SSURE T	EST FOR G	AS WELLS		Revised 12-1-5	
Pool	Poolinter-Platemed_CliffsR			Fo	Formation Planta Class				County_	An An		
											12-12-57	
											Sea Co.	
									1 ,19			
											ress. 11	
Date	of Comple	tion:_	124-17	•	Tubing Type Single-Bra Packer Reser				denhead-G. G. or G.O. Dual			
		?	,		_		ED DATA		•			
Test	ed Through	1 ((Cho	ke) (Type Ta _l	ne		
			Flow Data			-	Tubin	g Data	Casing 1			
No.	(Prover) (Line)	(Cho		ess.		Temp.		Temp.	Press.			
	Size	S	l z e p	sig	h _w	o _F .	psig	° _F .	psig	o _F .	of Flow Hr.	
SI 1		34.0		2		40 est.	775	60 ont	723	45		
2. 3. 4. 5.		-										
5. <u> </u>												
					F	LOW CAL	CULATIO	NS		- 		
No.	Coeffic	j		Pressur		e Flow Tem Factor		Gravity Factor	Compress. Factor		Rate of Flow Q-MCFPD	
- -	(24-Hour)		$\sqrt{h_{\mathbf{w}}p_{\mathbf{f}}}$	ps	sia .	Ft		Fg	Fpv		@ 15.025 psia	
1. 2. 3. 4. 5.						1,000		A.1783	1,60			
4.												
2•			,	<u> </u>								
						SSURE CA	LCU AT	CONS	•			
ravit	quid Hydro y of Liqui	id Hydro	ocarbons			cf/bbl. deg.		Spec: Spec:	ific Gravi ific Gravi	ty Sepa ty Flow	arator Gas ving Fluid	
c		 -	(1-e	·s <u>}</u>				^Р с—	N	Pc		
	Pw	2			:	7		·	Υ .			
No.	Pt (psia)	Pt ²	F _c Q	(F _c Q) ²	(F _c	Q) ² e ^{-s})	P_w^2	$P_c^2 - P_w^2$		P _W	
[. 2.						 ``	1	.764	590,205		y Pc	
L. 2. 3.										ļ		
										<u> </u>		
COMPAN			W IN		ara.	MCFPD;	n C.				arn .	
	and TITLE						RIA	1 Bano	- 0	af		
ITNES OMPAN	SSED										Manage	
		·				REMA	RKS			Ţ	CON COW N3 0 1328	
										AIF	DIST. 3	

INSTRUCTIONS

This form is to be used for reporting multi-point back pressure tests on gas wells in the State, except those on which special orders are applicable. Three copies of this form and the back pressure curve shall be filed with the Commission at Box 871, Santa Fe.

The log log paper used for plotting the back pressure curve shall be of at least three inch cycles.

NOMENCLATURE

- Q = Actual rate of flow at end of flow period at W. H. working pressure (P_W) . MCF/da. @ 15.025 psia and 60° F.
- P_c= 72 hour wellhead shut-in casing (or tubing) pressure whichever is greater. psia
- Pw Static wellhead working pressure as determined at the end of flow period. (Casing if flowing thru tubing, tubing if flowing thru casing.) psia
- Pt Flowing wellhead pressure (tubing if flowing through tubing, casing if flowing through casing.) psia
- Pf Meter pressure, psia.
- hw Differential meter pressure, inches water.
- Fg Gravity correction factor.
- Ft Flowing temperature correction factor.
- Fpv Supercompressability factor.
- n I Slope of back pressure curve.
- Note: If $P_{\rm W}$ cannot be taken because of manner of completion or condition of well, then $P_{\rm W}$ must be calculated by adding the pressure drop due to friction within the flow string to $P_{\rm t}$.

OIL CONSERVATION COMMISSION								
AZTEC DISTRICT OFFICE								
No. Copies Received 3								
DISTRIBUTION								
	NO. FURNISHED							
Operator								
Santa Fe								
Proration Office								
State Land Office								
U. S. G. S								
ransporter		<u> </u>						
File	1	1						