	9-881 a
(Teb	. 1951)

or (l	m 9- reb. 1	- 331 a 951)	•	(0.1ig	. Sgd.) ,.	A)
ř.	77.		C 32		· · · · · · · · · · · · · · · · · · ·	
			•			DE
			; ; ; ; ; ; ;			

Arte Co

(SUBMIT IN TRIPLICATE)

UNITED STATES **DEPARTMENT OF THE INTERIOR** GEOLOGICAL SURVEY

Land Office	Sents Pe
Lease No	186-03561
Unit	0

	1 1	AUDARAUETE DEC	T OF WITTE AUT		X
OTICE OF INTENTION TO DRILL		• ·	T OF WATER SHUT-OFF		
OTICE OF INTENTION TO CHANGE PLAN	1		F OF SHOOTING OR AC		
OTICE OF INTENTION TO TEST WATER		•	T OF ALTERING CASING		 \معدا
OTICE OF INTENTION TO RE-DRILL OR			F OF RE-DRILLING OR	REPAIR	
OTICE OF INTENTION TO SHOOT OR AC		•	T OF ABANDONMENT	2(E)	
OTICE OF INTENTION TO PULL OR ALT		SUPPLEMENTARY WE	LL MISTORY	. 0	95¢
OTICE OF INTENTION TO ABANDON WE	LL				
(INDICATE	ABOVE BY CHECK MARK NATE	RE OF REPORT, NOTIC	E, OR OTHER DATA)		- N W
			ا والاعتباد		
			April I		., 19.5
13. Section 1. (1/2 Sec. and Sec. No.)	(Twp.) (Ran		Meridian)		
tec Pictured Cliffs (Field)	(County or Sul	division)	(State or	Territory)	
(Field)	(00000)	 ,	,	••	
te names of and expected depths to ob		OF WORK	proposed casings; ind	cata mudding io	bs. cemes
ate names of and expected depths to of	bjective sands; show sizes, wi ing points, and all other	ignts, and lengths of important proposed	vork)	cate mudding jo	us, cemer
•	Potenta, and and				
			and the second second	Tìdds	
T.D. 2617*.	Perforased inc	2370-76 en			
T.D. 2517.	Perforaced fra foct. Sand-wate	2370-76 and r free with	Ma 100 galla	us unber.	
T.D. 2617°.	Perferesse from fock. Sand-make sand. Broakford	2370-76 ami r frac with pressure li	h,100 gallo	as mater,	
T.D. 2hl?". h shots per ho,000 lbs. pressure 109 h3.5 barrels	Performent from foot. Sand-make sand. Broakforn D Doe, final pr per minute. Re	2370-76 em r frec with pressure 12 escure 600 1	Ma 100 galla	as mater,	George
T.D. 2hl?". h shots per ho,000 lbs. pressure 109 h3.5 barrels	Performed from fect. Sand-make sand. Breakford D Dos., final pr	2370-76 em r frec with pressure 12 escure 600 1	h,100 gallo	us under, ating un rate	The
T.D. 2hl?". h shots per ho,000 lbs. pressure 109 h3.5 barrels	Performent from foot. Sand-make sand. Broakforn D Doe, final pr per minute. Re	2370-76 em r frec with pressure 12 escure 600 1	h,100 gallo	us under, ating un rate	
T.D. 2hl?". h shots per ho,000 lbs. pressure 109 h3.5 barrels	Performent from foot. Sand-make sand. Broakforn D Doe, final pr per minute. Re	2370-76 em r frec with pressure 12 escure 600 1	h,100 gallo	us under, ating un rate	
T.D. 2hl?". h shots per ho,000 lbs. pressure 109 h3.5 barrels	Performent from foot. Sand-make sand. Broakforn D Doe, final pr per minute. Re	2370-76 em r frec with pressure 12 escure 600 1	h,100 gallo	us under, ating un rate	
T.D. 2517'. L shots per 50,000 lbs. pressure 105 13.5 barrels 2390'. S I	Performed from foot. Sand-mate sand. Broakford D Dow, fisal pr per sinute. Ra D April 9, 1956.	2370-76 and r free with pressure 12 easure 600 1 n 2380° of 1	h,100 gallo 00 lbs., tro bs., injecti * taking lan	RECE	
T.D. 2hl?". h shots per ho,000 lbs. pressure 109 h3.5 barrels	Performed from foot. Sand-mate sand. Broakford D Dow, fisal pr per sinute. Ra D April 9, 1956.	2370-76 and r free with pressure 12 easure 600 1 n 2380° of 1	h,100 gallo 00 lbs., tro bs., injecti * taking lan	RECE	1052 1052
I.D. 2hi7. h shots per h0,000 lbs. pressure 10; i3.5 barrels 2390. S I	Performed Inches fort. Sand-make Sand. Breakfort D Ibe., final per printipe. Re it is a peril 9, 1958.	2370-76 and r free with pressure 12 easure 600 1 n 2380° of 1	h,100 gallo 00 lbs., tro bs., injecti * taking lan	RECE	1053 1053 1050 1050 1050
T.D. 2hi7. l. shots per lo,000 lbs. pressure 10; l3.5 barrels 2390. S I	Performed Inches fort. Sand-make Sand. Breakfort D Ibe., final per printipe. Re it is a peril 9, 1958.	2370-76 and r free with pressure 12 easure 600 1 n 2380° of 1	h,100 gallo 00 lbs., tro bs., injecti * taking lan	RECE	Will some of the second
I.D. 2hl7. h shots per h0,000 lbs. pressure 10; 13.5 barrels 2390. S I	Performed Inches fort. Sand-make Sand. Breakfort D Ibe., final per printipe. Re it is a peril 9, 1958.	2370-76 and r free with pressure 12 easure 600 1 n 2380° of 1	h,100 gallo 00 lbs., tro bs., injecti * taking lan	RECE	USS ON ON
T.D. 2517'. L shots per 50,000 lbs. pressure 105 13.5 barrels 2390'. S I	Performed Inches fort. Sand-make Sand. Breakfort D Ibe., final per printipe. Re it is a peril 9, 1958.	2370-76 and r free with pressure 12 easure 600 1 n 2380° of 1	h,100 gallo 00 lbs., tro bs., injecti * taking lan	RECE	1053 1053 1050 1050 1050 1050
I shots per 10,000 lbs. pressure 15 13.5 barrels 2390°. S I sompany 12772 OIL & ldress P. O. Bex. 756	Perference from foot. Sand-make sand. Broakford Disc., fissi pe per sinute. Re is April 9, 1956. nust receive approval in write OAS COMPART	2370-76 and r free with pressure 12 easure 600 1 n 2380° of 1	h,100 gallo 00 lbs., tro bs., injecti * taking lan	RECE	1053 nened
I.D. 2hl7. h shots per h0,000 lbs. pressure 10; 13.5 barrels 2390. S I	Perference from foot. Sand-make sand. Broakford Disc., fissi pe per sinute. Re is April 9, 1956. nust receive approval in write OAS COMPART	2370-76 and reference with pressure 12 and 1	h,100 gallo 00 lbs., tro bs., injecti * taking lan	RECE	1053 nened 100N

and the second second

HERE IN THE PERMITTER.

