

3-CCC  
1-H.L.Kendrick  
1-B. Parrish  
1-International  
1-TCA, 1-LDH  
1-T. Cowan  
1-F

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-122

Revised 12-1-55

MULTI-POINT BACK PRESSURE TEST FOR GAS WELLS

Pool BASIN DAKOTA Formation DAKOTA County San Juan  
Initial X Annual \_\_\_\_\_ Special \_\_\_\_\_ Date of Test 7/20/64  
Company Beta Development Co. Lease Oswell Federal Well No. 1  
Unit F Sec. A Twp. 29 N Rge. 11 W Purchaser El Paso Natural Gas Co.  
Casing 4 1/2" Wt. 10.5 I.D. 4.052 Set at 6675 Perf. 6504 To 6594  
Tubing 2 3/8" Wt. 4.70 I.D. 1.995 Set at 6581 Perf. Open To End  
Gas Pay: From 6504 To 6594 L 6581 xG .670 -GL \_\_\_\_\_ Bar.Press. 12.0  
Producing Thru: Casing \_\_\_\_\_ Tubing X Type Well Single - Gas  
Single-Bradenhead-G. G. or G.O. Dual  
Date of Completion: 7/10/64 Packer \_\_\_\_\_ Reservoir Temp. \_\_\_\_\_

OBSERVED DATA

Tested Through (Prover) (Choke) (Meter) Type Taps \_\_\_\_\_

No.	Flow Data					Tubing Data		Casing Data		Duration of Flow Hr.
	(Prover) (Line) Size	(Choke) (Prover) Size	Press. psig	Diff. h <sub>w</sub>	Temp. °F.	Press. psig	Temp. °F.	Press. psig	Temp. °F.	
SI						2012		2010		7 Days
1.		3/4"	331		81	331	81	1110		3 Hrs.
2.										
3.										
4.										
5.										

FLOW CALCULATIONS

No.	Coefficient (24-Hour)	$\sqrt{h_{wpf}}$	Pressure psia	Flow Temp. Factor F <sub>t</sub>	Gravity Factor F <sub>g</sub>	Compress. Factor F <sub>pv</sub>	Rate of Flow Q-MCFPD @ 15.025 psia
1.	12.3650		343	.9804	.9463	1.032	4.061
2.							
3.							
4.							
5.							

PRESSURE CALCULATIONS


Gas Liquid Hydrocarbon Ratio \_\_\_\_\_ cf/bbl.  
Gravity of Liquid Hydrocarbons \_\_\_\_\_ deg.  
F<sub>c</sub> \_\_\_\_\_ (1-e<sup>-s</sup>)  
Specific Gravity Separator Gas \_\_\_\_\_  
Specific Gravity Flowing Fluid \_\_\_\_\_  
P<sub>c</sub> 2026 P<sub>c</sub><sup>2</sup> 4104.6  
P<sub>w</sub> 1122 P<sub>w</sub><sup>2</sup> 1258.8

No.	P <sub>w</sub> P <sub>t</sub> (psia)	P <sub>t</sub> <sup>2</sup>	F <sub>c</sub> Q	(F <sub>c</sub> Q) <sup>2</sup>	(F <sub>c</sub> Q) <sup>2</sup> (1-e <sup>-s</sup> )	P <sub>w</sub> <sup>2</sup>	P <sub>c</sub> <sup>2</sup> -P <sub>w</sub> <sup>2</sup>	Cal. P <sub>w</sub>	P <sub>w</sub> P <sub>c</sub>
1.						1258.8	2645.8		
2.									
3.									
4.									
5.									

Absolute Potential: 5.348 MCFPD; n .75

COMPANY Beta Development Co.  
ADDRESS 234 Petroleum Club Plaza, Farmington, New Mexico  
AGENT and TITLE George I. Hoffman, Production Engineer  
WITNESSED H. McAnally  
COMPANY El Paso Natural Gas Co.

REMARKS



## INSTRUCTIONS

This form is to be used for reporting multi-point back pressure tests on gas wells in the State, except those on which special orders are applicable. Three copies of this form and the back pressure curve shall be filed with the Commission at Box 871, Santa Fe.

The log log paper used for plotting the back pressure curve shall be of at least three inch cycles.

## NOMENCLATURE

$Q$  = Actual rate of flow at end of flow period at W. H. working pressure ( $P_w$ ).  
MCF/da. @ 15.025 psia and 60° F.

$P_c$  = 72 hour wellhead shut-in casing (or tubing) pressure whichever is greater.  
psia

$P_w$  = Static wellhead working pressure as determined at the end of flow period.  
(Casing if flowing thru tubing, tubing if flowing thru casing.) psia

$P_t$  = Flowing wellhead pressure (tubing if flowing through tubing, casing if flowing through casing.) psia

$P_f$  = Meter pressure, psia.

$h_w$  = Differential meter pressure, inches water.

$F_g$  = Gravity correction factor.

$F_t$  = Flowing temperature correction factor.

$F_{pv}$  = Supercompressability factor.

$n$  = Slope of back pressure curve.

Note: If  $P_w$  cannot be taken because of manner of completion or condition of well, then  $P_w$  must be calculated by adding the pressure drop due to friction within the flow string to  $P_t$ .