


X



(SUBMIT IN TRIPLICATE)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

Land Office

Lease No. 078110

Unit

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL		SUBSEQUENT REPORT OF WATER SHUT-OFF	X
NOTICE OF INTENTION TO CHANGE PLANS		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF		SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL		SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE		SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING		SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL			

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

N.M. Federal #1

2-22

61

Well No. 3 is located 1030 ft. from N line and 1070 ft. from E line of sec. 1

1/4 Sec. and Sec. No.

29N

14W

NMPS

Basin-Cokota

San Juan

New Mexico

(Field)

(County or Subdivision)

(State or Territory)

The elevation of the derrick floor above sea level is 5589 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

The well was spudded 5 P.M. 1-5-61. A 12 1/2" hole was drilled to 33 1/2', set 8-5/8" 2 1/2" J-55 csg. to 327' and cemented w/275 sacks, cement circulated to surface. C 2 1/2 hrs. tested to 1000 PSI for 30 minutes. Drilled 7-7/8" hole to 6002'. ran 1 1/2" 11.6# J-55 csg. to 6001' and cemented w/300 sacks of 50-50 Fox mix. 200 lbs hrs. Top cement by temperature survey 1650'. Test csg. to 1000 PSI for 30 minutes.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Sunray Mid-Continent Oil Company

Address 166 Petroleum Center Building

Farmington, New Mexico

ORIGINAL SIGNED BY

By HAL M. STIERWALT

Engineer

Title