

X			

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office San Juan
Lesse No. 07610
State

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	X	SUBSEQUENT REPORT OF WATER SHUT-OFF	RECEIVED NOV 3 1963 U. S. GEOLOGICAL SURVEY FARMINGTON, NEW MEXICO
NOTICE OF INTENTION TO CHANGE PLANS		SUBSEQUENT REPORT OF STOPPING OR RESUMING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF		SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO REPAIR OR REPAIR WELL		SUBSEQUENT REPORT OF RE-GRADING OR REPAIR	
NOTICE OF INTENTION TO SIGHT OR ACQUIRE		SUBSEQUENT REPORT OF ADJUSTMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING		SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL			

(INDICATE ABOVE BY CHECKING MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

November 1, 1963

New Mexico Federal "T"

Well No. 3 is located 1031 ft. from [N] line and 1030 ft. from [W] line of sec.

1/4 Sec. 1

1/4 Sec.

1/4 Sec.

1/4 Sec.

Main Dakota

San Juan


The Nation

The elevation of the derrick floor above sea level is 5000 ft.

DETAILS OF WORK

(State nature of and expected depths to objectives under, show, sizes, weights, and lengths of proposed casing; indicate casing joints, cementing points, and all other important proposed work)

Production was shut off due to entry of mud into the casing. We propose to pull tubing and run a retrievable bridge plug and set at approximately 5000'. We will run a casing corrosion log to determine the area of corrosion. A squeeze packer will be run and the leak located. Cement will be pumped into the leak to cover the area of bad casing. The cement will be drilled out and the casing tested to 2000 psi for 30 minutes. The bridge plug will be pulled, tubing and packer run and well placed on production.



I understand that this plan of work must receive approval in writing by the Geological Survey before proceeding.

Company SAN JUAN OIL COMPANY

Address 101 University Blvd.

Denver, Colorado

By K. L. Hill
This Material Subject

