Form 3160-5 (June 1990)

UNITED STATES DEPARTMENT OF THE INTERIOR **BUREAU OF LAND MANAGEMENT**

PORM APPROVED Budget Bureau No. 1004-0135

Expires: March 31, 1993

| 5. Lesse Designation and Serial N | |
|-----------------------------------|--|

6. If Indian, Allottee or Tribe Name

SF 078110

| SUNDRY NOTICES A | ND REF | PORTS | ON WELLS |
|------------------|--------|-------|----------|
|------------------|--------|-------|----------|

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals

| SUBMIT IN TRIPLICATE | 7. If Unit or CA, Agreement Designation |
|--|--|
| 1. Type of Well Oil Gas Well Other P&A 2. Name of Operator | 8. Well Name and No. Federal I #3 |
| Dugan Production Corp. | 9. API Well No. |
| 3. Address and Telephone No. | 30 045 08861 |
| P.O. Box 420, Farmington, NM 87499 (505) 325-1821 | 10. Field and Pool, or Exploratory Area |
| 4. Location of Well (Footage, Sec., T., R., M., or Survey Description) | Basin Dakota |
| 1030' FNL & 1070' FWL Sec. 1, T29N, R14W, NMPM | 11. County or Parish, State San Juan, NM |
| CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, | REPORT, OR OTHER DATA |

TYPE OF ACTION Change of Plans

New Construction Non-Routine Fracturing Plugging Back Water Shut-Off

lo [0)[] Conversion to Injection Dispose Water e: Report results of multiple com

spirtion or Recompiction Report and Log form.) 13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Plugged well as follows:

1. Set CIBP @ 5800'.

- 2. Spot 13 cu. ft. class "B" cement @ 5800'. Dakota plug 5650' -5800'.
- 3. Spot 13 cu. ft. class "B" cement € 4975'. Gallup plug 4830' -49751.
- 4. Perforate 4⅓ casing @ 2273'. Spot 59 cu. ft. class "B" cement @ 2282'. Displace cement to 2122'. Mesa Verde plug 2122' -2273'.
- 5. Perforate @ 1270'. Spot 152 cu. ft. class "B" W/4% gel @ 1270'. Displace cement to 725'. Pictured Cliffs - Fruitland plug 725' - 1270'.
- 6. Perforate 43 casing @ 377'. Cement to surface with 133 cu. ft. class "B" w/4% gel. Surface plug 0' - 377'.

Job complete 6/6/95.

| 4. I hereby certify that the foregoing is true and correct Signed MM Charles | Operations Manager | Date6/8/95 |
|---|--------------------|------------|
| (This space for Federal or State office use) Approved by Conditions of approval, if any: | Tide | APPROVED |

Tide 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agencyor representations as to any matter within its jurisdiction