

X			

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Indian Agency Navajo Tribal
Allottee _____
Lease No. I-149-IND-6185

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF	X
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO REDRILL OR REPAIR WELL	SUBSEQUENT REPORT OF REDRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Navajo "C"

Farmington, New Mexico February 19, 1959

Well No. 1 is located 790 ft. from [N] line and 990 ft. from [W] line of sec. 1
NW/4 of Section 1 T29N R17W N.M.P.M.
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Wilcox San Juan New Mexico
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 4976 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Navajo "C" Well No. 1 - on February 13, 1959, ran induction electric log, microlog and sonic log at 5570'. 7-1/8" casing was set at 5570' with 150 sacks neat cement. After waiting on cement, casing and water shut-off were tested with 1000 pounds pressure for thirty minutes, which held with no drop in pressure. Top cement by temperature survey 5000'. Reduced hole to 6-1/8" at 5570' and resumed drilling operations.



I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Pan American Petroleum Corporation

Address Box 487
Farmington, New Mexico

ORIGINAL SIGNED BY
R. M. Bauer, Jr.

By _____
Title Field Engineer

