Budget Bureau No. 42-R358. Approval expires 12-31-60	4.
APPROVALEXDITES 12-31-80	

Form 9-331a (Feb. 1951)

(SUBMIT IN TRIPLICATE)

Land Offic	santa Te
Lease No.	078615

UNITED STATES DEPARTMENT OF THE INTERIOR

Unit Mortheast Blanco

GEOLOGICAL SURVEY Unit Agreement No. 1. Nec. 929

SUNDRY	NOTICES	AND	REPORTS	ON	WELLS
					The state of the s

	 RECEIVE	L
NOTICE OF INTENTION TO DRILL NOTICE OF INTENTION TO CHANGE PLANS NOTICE OF INTENTION TO TEST WATER SHUT-OFF NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL NOTICE OF INTENTION TO SHOOT OR ACIDIZE NOTICE OF INTENTION TO PULL OR ALTER CASING NOTICE OF INTENTION TO ABANDON WELL	 SUBSEQUENT REPORT OF WATER SHUT-OFF 1958 SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING SUBSEQUENT REPORT OF ALTERING CLEING SUBSEQUENT REPORT OF BENEFIT REPAIR SUBSEQUENT REPORT OF ABANDONMENT SUPPLEMENTARY WELL HISTORY	
(INDICATE ABOVE BY CHECK AND	 	

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

PORROVER			
		April 22	, 1958
Kovell			
Well No. 1-4 is located	d 1090 ft. from ${\bf S}$ line	and 1550 ft. from $\begin{Bmatrix} \mathbf{x} \\ \mathbf{W} \end{Bmatrix}$ line of sec.	24
SV/4 Section 24 (% Sec. and Sec. No.)	30N 8y	жери	
(1/4 Sec. and Sec. No.)	(Twp.) (Range)	(Meridian)	
Blanco Nesaverde (Field)	San Juan	New Mexico	
	(County or Subdivision)	(State or Territory)	

The elevation of the derrick floor above sea level is 6196 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Original TD 5357. Continual hole caving caused drill pipe to stick and on 3-25-58, set HOWGO DM Retainer at 4688 and plugged hole for whipstock with 200 sacks 45 gel cement with 1% calcium chloride and 1 lb. medium Tuf Plug per sack. Whips cocked new hole to TD of 5455.

On 3-31-58, ran 20 Jts 58 15.50\$ J55 casing as liner - 832' (with turned down collars) act at 5444' and hung at 4612' with Burns Plain Type Casing Hanger. Comented with 150 sacks 45 gel coment with \$ 15 Tuf Plug per sack. Tested casing with 2000 P31 for 30 minutes. Held OK. Coment plug back depth: 5424'. Top general at 4612'.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company	BLACKWOOD & MICHOLS COMPANY	oy une Geological Survey before operations may be commence	ed.
Address	P.O. 30X 1237		
***************************************	DURAHOO, COLORADO	Original Signed By DeLasso Loos Delasso Lo	808
		Title Field Superintendent	