

(SUBMIT IN TRIPLICATE)  
UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

Land Office Santa Fe  
Lease No. 0750  
Unit Dowell

## SUNDRY NOTICES AND REPORTS ON WELLS

|  |  |  |  |
|--|--|--|--|
| NOTICE OF INTENTION TO DRILL                   |  | SUBSEQUENT REPORT OF WATER SHUT-OFF        |  |
| NOTICE OF INTENTION TO CHANGE PLANS            |  | SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING |  |
| NOTICE OF INTENTION TO TEST WATER SHUT-OFF     |  | SUBSEQUENT REPORT OF ALTERING CASING       |  |
| NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL |  | SUBSEQUENT REPORT OF REDRILLING OR REPAIR  |  |
| NOTICE OF INTENTION TO SHOOT OR ACIDIZE        |  | SUBSEQUENT REPORT OF ABANDONMENT           |  |
| NOTICE OF INTENTION TO PULL OR ALTER CASING    |  | SUPPLEMENTARY WELL HISTORY                 |  |
| NOTICE OF INTENTION TO ABANDON WELL            |  |  |  |

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Well No. 3-A is located 390 ft. from N line and 390 ft. from E line of sec. 4  
S. 4 (1/4 Sec. and Sec. No.) 30N (Twp.) 6E (Range) T. 1 N. R. 1 E. (Meridian)  
Blanco (Field) San Juan (County or Subdivision) New Mexico (State or Territory)  
The elevation of the derrick floor above sea level is 6000 ft.

### DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

On May 13, 1951:

Run 6-7/8" - 20# - 5-75 casing using 110 joints set at 4763' cemented with 175 sacks Ideal Regular Cement and 2 sacks Flo Gel. Top of Cement by Temperature Survey 3900'. Total Depth 4763'. Hold 900' for 30 minutes.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company SAN JUAN PRODUCTION COMPANY

Address 100 North Court Avenue  
Farmington, New Mexico

By E. J. Coal  
Title Petroleum Engineer