



(SUBMIT IN TRIPLICATE)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

Land Office Santa Fe  
Lease No. SF 078530-A  
Unit 1 1/2 of Sec. 4

## SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL	

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

June 19, 1956

Well No. L. F. Murphy is located 1650 ft. from [N] line and 1650 ft. from [E] line of sec. 4  
NE 1/4 of Sec. 4 (1/4 Sec. and Sec. No.) 30N (Twp.) 8W (Range) 106W (Meridian)  
Blanco (Olancho) (Field) San Juan (County or Subdivision) New Mexico (State or Territory)

The elevation of the derrick floor above sea level is 6200 ft.

## DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

5 1/2" Casing landed at 5521. Cement drilled out to 5482. Logged and 5 1/2" casing perforated 5448 to 5534 w/ 228 bullets, water free. w/ 26,130 gal water and 30,000' sand pressures 1050' to 600' hq. 43.7 MPN. Set bridge plug 5040, perforated 5016 to 4946 w/ 140 bullets, water free. w/ 26,000 gal water and 30,000' sand pressures 1350' to 950' hq. 40.9 MPN. Drilled plug and CO out to 5474. Est. 12,000 MP. 2" EUE tubing landed at 5439. Tree set, well OK.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company DeBor-Taylor Oil CorporationAddress P. O. Box 1175Farmington, New MexicoBy [Signature]Title Dist. Supt.