For ()	m 9- Feb. 19	331 a 951)	

(SUBMIT IN TRIPLICATE)

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

Land Office	San	ta Fe
Lease No.	078	50-A
Unit	Eż	Sec. 5

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLANS	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO PULL OR ALTER CASIN	NGSUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL	
(INDICATE ABOVE BY	Y CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)
Moore Tell No. 6 is located 13	35 ft. from $\{N\}$ line and 1090 ft. from $\{E\}$ line of sec. 5
	depends
NET Sec. 5 T- (4 Sec. and Sec. No.) (Tw	30-N R-8-W N-M-P-M- wp.) (Range) (Meridian)
	San Juan New Mexico (State or Territory)
(Field)	(County or Subdivision) (State or Territory)
	DETAILS OF WORK
ing po	sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, ceme oints, and all other important proposed work)
eaned out well to T.D., tests 14, 86, 88, 90, 92, 94, 96, 16, 60 tons CO2. Perf. with 18, 32. Frac. with 67,400 gal 18, 18, 18, 18, 18, 18, 18, 18, 18, 18,	sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, come oints, and all other important proposed work) sed casing to 4000# psi, o.k. Perf. one hole each; 98, 7700, 02. Frac. with 67,000 gal. water, 50,00 one hole each @ 7583, 7608, 7611, 14, 17, 20, 23, water, 45,500# 40-60 sand, 56.5 tons CO ₂ . Perf. Trac. with 30,000# 40-60 sand, 20,000# 20-40 sand, orf. 7488-96 with 4 shots per foot. Frac. with 35, 20,000 cm. ft. CO ₂ . Ran 239 joints of 2-3/8" EUE ring well to clean up for test.
aned out well to T.D., tests 4, 86, 88, 90, 92, 94, 96, d, 60 tons CO2. Perf. with 32. Frac. with 67,400 gal hots per foot 7555-7564. Fr and 77,370 gal. water. Per er, 17,500# 20-40 sand and ing landed 7459. Now blow	ands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, come oints, and all other important proposed work) sed casing to 4000# psi, o.k. Perf. one hole each; 98, 7700, 02. Frac. with 67,000 gal. water, 50,00 one hole each 2 7583, 7608, 7611, 14, 17, 20, 23, one hole each 2 7583, 7608, 7611, 14, 17, 20, 23, water, 45,500# 40-60 sand, 56.5 tons CO2. Perf. rac. with 30,000# 40-60 sand, 20,000# 20-40 sand, orf. 7488-96 with 4 shots per foot. Frac. with 35, 20,000 ca. ft. CO2. Ran 239 joints of 2-3/8" EUE ring well to clean up for test.
aned out well to T.D., tests 4, 86, 88, 90, 92, 94, 96, 6, 60 tons CO2. Perf. with 32. Frac. with 67,400 gal shots per foot 7555-7564. Fr and 77,370 gal. water. Per er, 17,500# 20-40 sand and sing landed 7459*. Now blow	sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, come oints, and all other important proposed work) sed casing to 4000# psi, o.k. Perf. one hole each 98, 7700, 02. Frac. with 67,000 gal. water, 50,00 one hole each 27583, 7608, 7611, 14, 17, 20, 23, water, 45,500# 40-60 sand, 56.5 tons CO2. Perf. rac. with 30,000# 40-60 sand, 20,000# 20-40 sand, orf. 7488-96 with 4 shots per foot. Frac. with 35, 20,000 ca. ft. CO2. Ran 239 joints of 2-3/8" EUE ring well to clean up for test.
eaned out well to T.D., tests 14, 86, 88, 90, 92, 94, 96, 16, 60 tons CO2. Perf. with 18, 32. Frac. with 67,400 gal 18, 18, 18, 18, 18, 18, 18, 18, 18, 18,	sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, come coints, and all other important proposed work) sed casing to 4000# psi, o.k. Perf. one hole each 98, 7700, 02. Frac. with 67,000 gal. water, 50,00 one hole each 27583, 7608, 7611, 14, 17, 20, 23, water, 45,500# 40-60 sand, 56.5 tons CO2. Perf. Trac. with 30,000# 40-60 sand, 20,000# 20-40 sand, orf. 7488-96 with 4 shots per foot. Frac. with 35, 20,000 ci. ft. CO2. Ran 239 joints of 2-3/8" EUE ring well to clean up for test. Corporation Orginal signed by Original signed by
aned out well to T.D., tests 4, 86, 88, 90, 92, 94, 96, d, 60 tons CO2. Perf. with 32. Frac. with 67,400 gal. hots per foot 7555-7564. Fr and 77,370 gal. water. Per er, 17,500# 20-40 sand and sing landed 7459'. Now blow	ands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cemeroints, and all other important proposed work) ded casing to 4000# psi, o.k. Perf. one hole each; 98, 7700, 02. Frac. with 67,000 gal. water, 50,000; one hole each 2 7583, 7608, 7611, 14, 17, 20, 23; one hole each 2 7583, 7608, 7611, 14, 17, 20, 23; water, 45,500# 40-60 sand, 56.5 tons CO ₂ . Perf. Trac. with 30,000# 40-60 sand, 20,000# 20-40 sand, orf. 7488-96 with 4 shots per foot. Frac. with 35, 20,000 cas. ft. CO ₂ . Ran 239 joints of 2-3/8" EUE ring well to clean up for test. Corporation Onginal signed by A R twoson