STATE OF NEW MEXICO ENERGY and MINERALS DEPARTMENT

51

Location of Well: E262909

DITE 3

Page 1

OIL CONSERVATION DIVISION NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST

Operator: AMOCO PRODUCTION COMPANY Lease/Well #:FLORANCE 027A Meter #:95289 RTU:1-157-04 County:SAN JUAN

	NAME RESE	RVOIR OR F	OOL		TYPE PROD	METHOD PR	מאן עט	EDIUM PROD	
PR OMP	FLORANCE 027A FT 95289				GAS	FLOW		TBG	
IR MP	FLORANCE 027A BMV 451221				GAS	FLOW		TBG	
	l	PRE	E-FLOW	SHUT-IN	PRESSURE DA	TA			
	Hour/Date	Shut-In	Leng	th of Tim	e Shut-In	SI Press.	PSIG	Stabilzed	
PR OMP	08/01/94		72 1.0		(63		yê)		
VR OMP	08/01/94			72	mo	60		yes !	
	1		l	FLOW TEST	DATE NO.1	l		, 1	
omme	nced at (ho	our,date)*		1559.1	60 ps 1 180	-180-18D	Produci	ng (Upr(Lw	
TIME LAPSED (hour, date) SINCE		1	PRESSURE Upper Lowe		Prod Temp.	REMARKS			
08/01/94		Day	1 /50		42		Both Zones SI Both Zones SI		
08/02/94		Day 2		160	60				
08/03/94		Day 3		160	60		Bot	th Zones SI	
08/04/94		Day			60		flow laws gare		
08/05/94		Day	Day 5 /65		130)	1.	., 0"	
08/06/94 Day		6	170	110		11			
)il:_	uction rate	during to	h-a-d	on D.Tested	BBLs in theu (Orifi	Hrs	Grant	av GOR _ ER	
as:			MID-T	EST SHUT-	IN PRESSURE	DATA		•	
JPR COMP	Hour, Dat	e SI Lei	ngth o	f Time SI	SI Press	DE	tabili CEII AUG 10	IUI	

FLOW TEST NO. 2

Commonced at thour, dat	0) + +		Zone producing (Upper or Lower):					
THE	LAPSED TIME SINCE * *	PRESSURE		PROD. ZONE				
frour, detail		Upper Completion	Lower Completion	TEMP,	REMARKS			

Production rate di	ring test				•			
Oil:	BOPI	D based on	Bbls. in	Hours.	Grav GOR			
):			
Remarks:								
								
I hereby certify the	at the information	on herein containe	ed is true and con	mplete to the best	of my knowledge.			
Approved AUG New Mexico Oil	Conservation D	ivision		Operator Amoco Production Company				
By Charle		1			how Bradshaw &			
-			TideField Tech					
Tide DEPUTY OF	L & GAS INSPECT	UK, DIST. #5	D	Date 8 -9 -9				

NORTHWEST NEW MEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- 1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- 2. At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one hone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.
- 5. Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.
- 6. Flow Test No. 2'shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except

- that the previously produced 2000 shall remain shut in while the 2000 which was previously shut in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow-period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests: immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the coochusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.

24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the securacy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.

8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packet Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).