Location of Well: E262909 Page 1

OIL CONSERVATION DIVISION NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST

| Operator: | AMOCO | PRODUCTION | COMPANY | Lease/Well | #:FLORANCE 02 | 7 A |
|-----------|---------|------------|----------|------------|---------------|------------|
| Operator. | HIOCO | 1100001 | | - 04 | Country CAN | TTTAN |
| Meter | #:95289 |) | RTU:1-15 | /-04 | County:SAN | U UPIN |

| Met | er #:95289 | RTU | J:1-157-04 | C | ounty:SAN J | UAIN | |
|-----------------------|--------------------|-----------------------|----------------|-------------------|---------------|---------------------------------------|--|
| | NAME RESE | RVOIR OR POOL | | TYPE PROD | METHOD PRO | D MEDIUM PROD | |
| PR OMP | FLORANCE 0 | 27A FT 95289 | | GAS | FLOW | TBG | |
| WR OMP | FLORANCE 0 | 27A BMV 45122 | 21 | GAS | FLOW | TBG | |
| | | PRE-FLO | OW SHUT-IN I | PRESSURE DA | ATA | · · · · · · · · · · · · · · · · · · · | |
| | Hour/Date | Shut-In Le | ngth of Time | e Shut-In | SI Press. | PSIG Stabilzed | |
| PR OMP | 04/28/95 | | 72 Hes | | 160 | У | |
| WR OMP | 04/28/95 | | 72 HRS | | 125 | у | |
| | | | FLOW TEST | DATE NO.1 | I | I | |
| omme. | nced at (ho | our,date)* | | | Zone Pi | roducing (Upr/Lwr) | |
| (hc | TIME our, date) | LAPSED TIME SINCE* | Øn PR Upper | ESSURE - Lower | Prod Temp. | REMARKS | |
| 04/28/95 Day | | Day 1 | 120 | 88 | | Both Zones SI | |
| 04/29/95 | | Day 2 | 136 | 95 | | Both Zones SI | |
| C | 04/30/95 | Day 3 | 150 | 110 | | Both Zones SI | |
| C | 05/01/95 | Day 4 | 160 | 125 | | FLOW UPPER ZONE | |
| C | 05/02/95 | Day 5 | 120 | 1201 | | n n n | |
| (| 05/03/95 | Day 6 | 120 | 120 | | 10 C C1 | |
| Produ Dil: Gas: | uction rate | י יין ויין | ed on | -11CG (OTT | | GravGOR :):METER | |
| UPR COMP | | e SI Length | of Time SI | SI Press | s. PSIG St | Chilised (Yes/no) | |
| LWR COMP | | | | | | oil con. Div. | |
| | | | Continue on | reverse s | ide) | DIST. 3 | |

FLOW TEST NO. 2

| Commenced at thour, dated # # | | | | Zone producing (Upper or Lower) | | |
|-------------------------------|------------------------------------|-------------------|--------------------|---------------------------------|--|--|
| THAG | LAPSED TIME | . PRESSURE | | | | |
| flour, datel | SINCE ** | Upper Completion | Lewer Completion | PROD. ZONE TEMP. | REMARKS | |
| | | | | | | |
| ···· | | | | | | |
| | |] | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | **** | | | | |
| | | | | | THE PARTY OF THE P | |
| | 1 . | | 1 | | | |
| roduction rate | | | | | | |
|)il: | BOP! | D hased on | Rhia ia | • | Grav GOR | |
| | | - DECG OII | DDB. III | Hours. | Grav GOR | |
| 25: | | MCFT | PD: Tested thru | (Orifice or Meter): | | |
| emarks: | | | | • | | |
| | | | | | | |
| | | | | | | |
| hereby certific | that the inferred | | | | | |
| neicoj cenny | that the information | n netein containe | ed is true and con | oplete to the best | of my knowledge. | |
| pproved | Johnny Rober Dil Conservation D | neen | 19 0 | | | |
| New Mexico | Dil Conservation D | ivision | / | All All | moco Production Company | |
| | MAY 0 9 19 | 995 | Ву | | heni Bradshaw & | |
| y | | | | | | |
| | DEPUTY OIL & GAS II | VSPECTOR | | | eld Tech | |
| de | | | D ₂ | te . 5 | 14/95 | |
| | | | | *** | | |

NORTHWEST NEW MEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- 1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been distrutbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one lone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.
- 3. Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.
- 6. Flow Test'No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except

- that the previously produced 2000 shall remain shut-in while the 2000 which was previously shut-in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow-period, at fifteen-minute intervals during the first hour thereof, and at bourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests: immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.

24-hour oil zone tesu: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.

8. The results of the above-described tests shall be filed in triplicate within 13 days after completion of the test. Tests shall be filed with the Axtec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Lexkage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).