

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

SF 078581

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

Northeast Blanco Unit

Agrmt. No. 1, Sec. 929

8. FARM OR LEASE NAME

Northeast Blanco Unit

9. WELL NO.

104A

10. FIELD AND POOL, OR WILDCAT

Blanco Mesaverde

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

D-1-30N-8W

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

6402' GL

12. COUNTY OR PARISH

San Juan

13. STATE

New Mexico

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

☐

PULL OR ALTER CASING

☐

FRACTURE TREAT

☐

MULTIPLE COMPLETE

☐

SHOOT OR ACIDIZE

☐

ABANDON*

☐

REPAIR WELL

☐

CHANGE PLANS

☐

(Other)

☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

☒

REPAIRING WELL

☐

FRACTURE TREATMENT

☐

ALTERING CASING

☐

SHOOTING OR ACIDIZING

☐

ABANDONMENT*

☐

(Other) Case & Cement

☒(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

- 3-11-78 Moved on location and rigged up. Spudded 12-1/4" surface hole @ 8:30 PM. Drilled to 240' KB.
- 3-12-78 Ran 6 jts (224') 9-5/8" 36# H-40 ST&C Rge 3 Casing and set at 238' KB, cemented with 150 sacks of Class "B" with 2% CaCl₂, cement circulated. Plug down at 7:30 AM. W.O.C. twelve hours, tested casing to 800 PSI for thirty minutes, held O.K.
- 3-17-78 Drilled 8-3/4" hole to 3630' KB. Ran Induction Electric, FDC and SNP logs.
- 3-18-78 Ran 97 jts (3618') 7" 23# K55 ST&C Rge 3 Casing and set at 3630'KB; cemented with 200 sacks Howco Lite with 1/4# Flocele and 100 sacks Class "B" with 2% CaCl₂ and 1/4# Flocele/sack. Plug down at 4:30 P.M. Top cement by temperature survey 2200'.
- 3-20-78 Gas drilled 6-1/4" hole to 6050' KB. Ran Gamma Ray Induction, FDC and SNP logs.
- 3-21-78 Ran 79 jts. (2596') 4-1/2" 10.5# K55 ST&C Rge 2 Liner with Baker Oil Tool Pack off and set @ 6050'; Float collar at 6016', top of liner at 3454' KB; cemented with 300 sacks of 50-50 Poz with 2% Gel, 0.6% FLA, 6-1/4# Gilsonite/sack and 1/4# Flocele per sack. Plug down at 11:45 P.M.; Reversed out 17 bbls cement. Released rig. Waiting on completion.

18. I hereby certify that the foregoing is true and correct

SIGNED

B. B. Whitemburg

TITLE Drilling Supervisor

DATE 3-27-78

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

57