

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUBMIT IN TRIPPLICATE\*  
(Other instructions on re-  
verse side)

Form approved.  
Budget Bureau No. 42-R1424

5. LEASE DESIGNATION AND SERIAL NO.

SF-077710

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Hardie

9. WELL NO.

68

10. FIELD AND POOL, OR WILDCAT

Fulcher Kutz P.C.

11. SEC., T., R., OR BLK. AND

Sec. 14-T29N-R12W

N.M.P.M.

12. COUNTY OR PARISH 13. STATE

San Juan

N.M.

1. OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

R & G Drilling Company

3. ADDRESS OF OPERATOR

c/o Walsh Engineering, Box 254, Farmington, NM

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.)

See also space 17 below.)

At surface

990' FSL, 800' FWL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

5781'GR, 5791'KB, 5792' DF

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

☐  
☐  
☐  
☐

PULL OR ALTER CASING

☐  
☐  
☐  
☐

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON\*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

☒  
☐  
☐

REPAIRING WELL

ALTERING CASING

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

ABANDONMENT\*

(Other)

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

5-19-78 Spud well

5-19-78 T. D. 168'

Ran 4 jts. 8-5/8", 24.0 lb, K-55 casing (157.00') set at 168.001 with 150 sacks Class "B" cement with 3% Calcium Chloride and 6 1/4 lb. Flocele per sack. Cement circulated. Test with 500 psig. Test O.K.

5-23-78 T.D. 1982'

Ran 49 jts., 4 1/2", 10.50 lb, K-55 casing (1967.15') set at 1978.15' with 150 sacks 65/35 Pozmix (12% Gel) With 6 1/4 lbs. Gilsonite per sack followed by 150 sacks 50/50 Pozmix with 6 1/4 lbs. Gilsonite per sack. Cement circulated.

RECEIVED

For: R & G Drilling Company

18. I hereby certify that the foregoing is true and correct

SIGNED

Ewell N. Walsh, P.E.

TITLE

President, Walsh Engr. & Production Corp.

DATE

6-6-78

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY: