

| | |
|------------------------|---|
| NO. OF COPIES RECEIVED | 3 |
| DISTRIBUTION | |
| SANTA FE | 1 |
| FILE | |
| U.S.G.S. | |
| LAND OFFICE | |
| OPERATOR | 1 |

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

| | | |
|--|--|--|
| 1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER <input type="checkbox"/> | | 5a. Indicate Type of Lease State <input type="checkbox"/> Fee <input checked="" type="checkbox"/> |
| 2. Name of Operator Amoco Production Company | | 5. State Oil & Gas Lease No. |
| 3. Address of Operator 501 Airport Drive Farmington, NM 87401 | | 7. Unit Agreement Name |
| 4. Location of Well UNIT LETTER J, 1850 FEET FROM THE South LINE AND 1490 FEET FROM THE East LINE, SECTION 28, TOWNSHIP 29N, RANGE 10W, NMPM. | | 8. Farm or Lease Name Sullivan Gas Com "C" |
| | | 9. Well No. 1E |
| | | 10. Field and Pool, or Wildcat Basin Dakota |
| 15. Elevation (Show whether DF, RT, GR, etc.) | | 12. County San Juan |

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐
OTHER ☐

PLUG AND ABANDON ☐
CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐
COMMENCE DRILLING OPNS. ☐
CASING TEST AND CEMENT JOBS ☐
OTHER Set Intermediate and Production Casing ☒
ALTERING CASING ☐
PLUG AND ABANDONMENT ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Drilled 8-3/4" hole to 2185'. Set 7", 20# casing at 2185' and cemented with 275 sx "B" cement, 6% Gel, 2# medium Tuf Plug 1 sx, and 0.8% fluid loss additive. Tailed in with 100 sx class "B" Neat cement.

Drilled 6-1/4" hole to total depth of 6510' and set 4-1/2", 11.6# casing at 6508'. Cemented with 370 sx class "B" cement, 50:50 Poz, 6% Gel, 2# Medium Tuf Plug 1 sx, and 0.8% fluid loss additive. Tailed in with 100 sx class "B" Neat cement.

Drilling rig released on 10-19-79.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

Original

SIGNED E. E. SVOJAK

TITLE Dist. Adm. Supr.

DATE 10/29/79

Original

Mendriek

APPROVED BY

TITLE

DATE 1979

CONDITIONS OF APPROVAL, IF ANY: