

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-1135
Expires September 30, 1990

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

5. Lease Designation and Serial No.

SE-080246

6. If Indian, Allottee or Tribe Name

7. If Lnt or C.A. Agreement Designation

8. Well Name and No.

Florance 124

9. API Well No.

30 045 24126

10. Field and Pool, or Exploratory Area

Blanco Mesaverde

11. County or Parish, State

San Juan, New Mexico

SUBMIT IN TRIPLICATE

1. Type of Well

☐ Oil Well ☐ Gas Well ☒ Other

2. Name of Operator

Amoco Production Company

Attn: John Hampton

3. Address and Telephone No.

P.O. Box 800, Denver, Colorado 80201

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

635' FNL, 2020" FWL

Sec. 27, T29N-R9W NE/NW

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☐ Notice of Intent

☒ Subsequent Report

☐ Final Abandonment Notice

TYPE OF ACTION

☒ Abandonment

☐ Recompleton

☐ Plugging Back

☐ Casing Repair

☐ Altering Casing

☐ Other

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut-Off

☐ Conversion to Injection

Note: Report results of multiple completion on Well Completion or Recompleton Report and Log form 1

13. Describe Proposed or Completed Operations. Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.*

Amoco Production Company plugged and abandoned the Cathodic Protection well associated with the above referenced gas well.

(Ground bed had no Anode wires coming from well. Wires had been cut-off and steel plate welded over 6" csg. Csg was cut off, has cement plug.)

1. Drilled cmt. plug from surf. to 14'.

2. Drilled and circ. out Gravel from 14' to 120'.

3. Circ. out Coke Breeze from 120' to 250'.

4. Drilled from 250' to 280' and circ.

5. Cemented back to surface with 82 sx Portland class B w/ 1/4 lb/sk Floccel @ 15.3 PPG. (Plugged in place 1900 hrs 5/12/90).

6. Backfilled pit and clean area.

If you have any questions please contact Cindy Burton @ 830-5119.

APPROVED

SEP 13 1990

16 AREA MANAGER

14. I hereby certify that the foregoing is true and correct

Signed

J. Hampton/CB

Title

Sr. Staff Admin. Supv.

Date

8/16/90

(This space for Federal or State office use)

Approved by

Conditions of approval, if any:

Title

Date