STATE OF NEW MEXICO ENERGY and MINERALS DEPARTMENT J-5-30.8

Location of Well: J053008 Page 1

OIL CONSERVATION DIVISION NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST

Operator: AMOCO PRODUCTION COMPANY Lease/Well #:MOORE 006E

Me	ter #:95967		RTU:	0-000-00		ounty:	SAN JUAI	N	
	NAME RESERVOIR OR POOL				TYPE PROD	METHO	D PROD	PROD MEDIUM PROI	
IPR COMP	MOORE 006E	FT 95967	GAS	FL	FLOW		TBG		
WR OMP	MOORE 006E	DK 93956		GAS	FL	FLOW		TBG	
	1	PRE	-FLOW	SHUT-IN I	PRESSURE DA	TA	····	I	
	Hour/Date Shut-In		Length of Time		e Shut-In	SI Press. PS		IG S	Stabilzed
PR OMP	06/07/95		72			41		: izea	
WR OMP	06/07/95	7.2			316			NA	
		I			DATE NO.1				
omme	nced at (ho	our,date)*				Zo	ne Prod	ucing	(Upr/Lwr
TIME (hour, date)		LAPSED TIME SINCE*		PRI Upper	ESSURE Lower	i	od mp.	REMARKS	
06/07/95 6/12/95 06/08/95 6/13-95 6/10/95		Day 1		362/405	3	85	5		Zones SI
				362/405	3 2	85		Both Zones SI	
		Day 3	363/4/		293			Both Zones SI	
6/15/95		Day 4		363/4/0	376		HA.	HAUR NEVEL PRODUCE Ft. ZONE, LOWELL	
6116195		Day	1	363/4/0	376		í		DK Zone
	111/95	Day (363/1/10	236		la	10 de	you on
	oction rate	BOPD I	oased MFCPD	:Tested t	BBLs in heu (Orific N PRESSURE	ce or M	s Meter):M	Grav_ IETER	GOR
JPR COMP	Hour, Date	e SI Leng	gth of	Time SI	SI Press	. PSIG	Stabi	lized CE	(yes/no)
LWR COMP	6/12/95 1:00 A.M.		······································				- - -	JUN 2 (1995 U
			(Cor	ntinue on	reverse sign	de)		COX	b DIV

FLOW TEST NO. 2

Commenced at Flour, 64	(b) T T		Zone producing (Upper or Lawers			
THE	LAPRED TIME	PRESSURE		PROD ZONE		
frour, desay	SINCE * *	Upper Completion	Lewer Completion	TEMP.	REMARKS	
	ļ					
	ļ					
•	 					
		1	ļ			
	ļ	**************************************		THE PARTY OF THE P	The state of the s	
		·	7	1		
Production rate d	uring test				•	
O:I.	BOD.	n. L.	D11 1		_	
Oii:	DOP	D based on	BDIS. II	n Hours.	Grav GOR	
		MCF	PD: Tested thru	(Orifice or Merer)):	
				(Orane or ineter)		
Remarks:						
						
I hereby certify th	at the informati	on harain marain	ad in tops and a	omplete to the best		
				onapiete to the pest	t of my knowledge.	
Approved	Johnny Rol	unsen	19 (Operator	_	
New Mexico O	il Conservation I	Division	- ,		0.0	
	JUN 21	1995	1	Ву	THE HE NOW	
_			_	1 .		
Ву	DEPUTY OIL & GA	SINSPECTOR		Title	are fichauteryst	
Tide	DEI OTT OIL IX ON		1	0220	nelses April Le Tichnelogist 117/95	
****			<i>i</i>	JAUE		

NORTHWEST NEW MEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- 1. A packer leakage test shall be commenced on each multiply completed well within screen days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within screen days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- 2. At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3. The packet leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain thut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one lone of the dual completion shall be produced at the normal rate of production while the other zone remains shur-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial packet leakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.
- 5. Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.
- Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except

- that the previously produced zone shill remain shut in while the zone which was previously shut in it produced.
- 7. Pressures for gui-zone term must be measured on each zone with a deadweight pressure gauge at time intervals at follows: 3 hours term: immediately prior to the beginning of each flow-penod, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day term immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and manediately prior to the coordinion of each flow period. Other pressures may be taken at desired, or may be requested on wells which have previously shown questionable test data.

14-hour oil zone testi all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least revice, once at the beginning and once at the end of each test, with a desidenght pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas sooe.

8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Azter District Office of the New Meson Oil Conservation District on Northwest New Meson Packet Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas 200es only) and gravity and GOR (oil 200es only).