

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other ☐
2. NAME OF OPERATOR
Tenneco Oil Company
3. ADDRESS OF OPERATOR
Box 3249, Englewood, Co 80155
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1120' FSL, 1100' FWL "M"
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:


TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

SUBSEQUENT REPORT OF:

☐
☒
☐
☐
☐
☐
☐
☐

5. LEASE
NM - 0468126
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME
Callow
9. WELL NO.
A-1E
10. FIELD OR WILDCAT NAME
Basin Dakota
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec 27, T29N, R13W
12. COUNTY OR PARISH
San Juan
13. STATE
NM
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)
5375' ground

(NOTE: Report results of multiple completion or zone change on Form 9-331-C)



17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

4/8/81 MIRUSU. Install BOP. RIH w/ tbg and drag bit. Drilled 2' of DV tool. Stopped making hole. Circ hole clean.
4/9/81 POOH w/ tbg and bit. RIH w/ tbg and cone duster mill and finish drilling out DV tool. Finish RIH w/ tbg. Tag latch down collar @ 5866'. Drill out latch collar PBTD @ 5908'. Pressure test to 3500 PSI. Test good. Circ'd hole clean w/ 1% KCL water spot 500 gals 7½% DI-HCL @ 5845'. POOH w/ tbg and mill.
4/10/81 Ran GR/ CCL. Perf Dakota w/ 3 1/8" gun @ 2 JSPF as follows; 5724-34', 5738-56', 5818-28', 5832-48'. Total 54' 108 holes. Estab rate w/ 1% KCL water: 44BPM @ 3200 PSI. Acidize w/ 2200 gals 15% weighted HCL and 152 balls. Ball off complete. RIH w/ wireline junk basket to PBTD.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Carley Watkins TITLE Asst. Div. Adm. Mgr. DATE April 16, 1981

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY: _____

APR 24 1981

*See Instructions on Reverse Side

FARMINGTON DISTRICT
BY Carley Watkins